



UPC Code: 07847768394 Country Of Origin: China

# T5832-GY

#### **Brand Features**

The Leviton USB Charger/Tamper-Resistant Duplex Receptacle offers two highpowered USB Ports with 3.6A of charging power and two 20A or 20A/125V Tamper-Resistant Receptacles. It has the capability to charge two USB powered electronic devices utilizing its two USB Ports, leaving the two Tamper-Resistant Receptacles free for other uses. The Leviton USB Charger/Tamper-Resistant Duplex Receptacle is designed to charge tablets, smart and mobile phones, gaming devices, e-readers, digital cameras and a host of other electronic devices.

#### **Item Description**

Combination Duplex Receptacle/Outlet and USB Charger. 20 Amp, 125 Volt, Decora Tamper-Resistant Receptacle/Outlet, NEMA 5-20R. 3.6 Amps, 5VDC, 2.0 Type A USB Chargers. Grounding, Side Wired &Back Wired - Gray.

#### **Technical Information**

Electrical Specifications Amperage: 20 A Grounding: Grounding Horsepower Rating: 20A-1 HP Ratings: 20A-125V Receptacle Voltage: 125V AC

Environmental Specifications Flammability: Rated V-0 per UL 94 Operating Temperature: -10°C to 40°C

Material Specifications Body Material: Thermoplastic Color: Gray Cover Material: Thermoplastic Strap Material: Steel Mechanical Specifications

Product ID: Stamped on Strap Terminal Accom.: 14-12 AWG

Terminal ID: Brass-Hot Black-Hot White-Neutral Green-Gnd

Termination: Back & Side

Torque Range: 12-14 inch pounds

Product Features Color: Gray

**Grade:** Residential/Commercial Specification Grade

Amperage: 20 A

Standards and Certifications FCC Part 15: Class B for Residential Compliance Listed: cCSAus NOM: 057 Warranty: 5 Year Limited

#### **Features and Benefits**

- Perfect for use in residential applications such as kitchens, bedrooms and home offices and in commercial applications such as hotels, airports, restaurants and cafes, salons, office cubicles and college dorm rooms
- Smart chip recognizes and optimizes the charging requirements of individual devices
- USB Ports are positioned vertically providing more space for maneuvering and reducing stress on USB cables
- Compatible with USB 2.0 devices
- Fits in a standard wallbox, is compatible with standard wallplates and can be multi-ganged with other devices
- Easy to install. Can replace existing outlets

# SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

# Leviton Manufacturing Co., Inc.

# 201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

# Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

## Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

### Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

# Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

