

Catalog Number: Item Description: UPC Code:

U3791N-RXL-150-5T9 200A 5T RL OU HD LVR MAIN 784572288287

| Brand Name: | Milbank |
|--|--|
| Туре: | Ringless Meter Socket |
| Application: | Meter Socket With Main |
| Standard: | UL Listed |
| Voltage Rating: | Up to 240 Volts Alternating Current |
| Amperage Rating: | 200 Ampere Continuous |
| Phase: | 1 Phase |
| Frequency Rating: | 60 Hertz |
| Number Of Cutouts: | 1 |
| Cutout Size: | 150 Ampere Main Breaker |
| Cable Entry: | Overhead and Underground |
| Terminal: | Lay in Line Side and Single Mechanical |
| Mounting: | Surface Mount |
| Enclosure: | Type 3R, G90 Galvanized Steel with Powder Coat Finish |
| Additional Specifications: Number of Jaws:5 Terminal | |



Number of Jaws:5 Terminal

Hub Opening and Closing Plates:Large Hub Opening Adapted to Small Closing Plate Bypass Provision:Lever Bypass

Number Positions:1 Position

Utility requirements may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must always be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.