



**Catalog Number:** U5168-XTL-100-KK  
**Item Description:** 200A 4T RL OU MAIN 8CRT  
**UPC Code:** 784572475328

**Brand Name:** Milbank  
**Type:** Ringless Meter Socket  
**Application:** Meter Socket With Main And Load Center  
**Standard:** UL Listed  
**Voltage Rating:** Up to 240 Volts Alternating Current  
**Amperage Rating:** 200 Ampere Continuous  
**Phase:** 1 Phase  
**Frequency Rating:** 60 Hertz  
**Number Of Cutouts:** 1  
**Cutout Size:** 100 Ampere Main Breaker  
**Cable Entry:** Overhead and Underground  
**Terminal:** Lay in Line Side and Single Mechanical Load Side  
**Mounting:** Surface Mount  
**Enclosure:** Type 3R, G90 Galvanized Steel with Powder Coat Finish



**Additional Specifications:** Line Side Wire Range:6 AWG - 350 kcmil  
AIC or SCCR Rating: Please Contact Factory  
Optional 5th Terminal Position:3 O'Clock, 9 O'Clock  
Maximum Amperage:100 Maximum Ampere  
Number of Jaws:4 Terminal  
Hub Opening and Closing Plates:Twin Small Closing Plates  
Bypass Provision:Horn Bypass  
Number Positions:1 Position

*Utility requirements may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must always be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.*