

Catalog Number: Item Description: UPC Code:

U5882-X 200A 4T RL OU 2P MAIN 784572520332

Brand Name:	Milbank
Туре:	Ringless Meter Socket
Application:	Meter Socket With Main
Standard:	UL Listed
Voltage Rating:	Up to 240 Volts Alternating Current
Amperage Rating:	200 Ampere Continuous
Phase:	1 Phase
Frequency Rating:	60 Hertz
Cable Entry:	Overhead and Underground
Terminal:	3/8 Inch Stud Line Side and Single Mechanical Load Side
Mounting:	Surface Mount
Enclosure:	Type 3R, G90 Galvanized Steel with Powder Coat Finish
A dellation of Consections	



Additional Specifications:

Number of Jaws:4 Terminal

Hub Opening and Closing Plates:Large Closing Plate

Bypass Provision:No Bypass

Number Positions:2 Positions

Utility requirements may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must always be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

		FEATURE TABLE
ITEM	QTY	DESCRIPTION
А	4	TRANS. MNTG.EMBOSS
В	1	1/4 SOLID K.O.
С	2	7∕8 SOLID K.O.
D	1	1⁄2, 3⁄4, 1 CONC. K.O.
Е	4	1¼, 1½, 2, 2½ CONC. K.O.
F	1	2, 21/2, 3 CONC. K.O.





