

**Product Specification Sheet** 

## 40480J

## 1/4-20 HEX SERTD FLANG NUT ZP

UPC: 085937002761

UNSPSC: 31161727

Commodity: Hexagonal nuts

Country of Origin: **Not Available** 

Hex nut with an enlarged circular base flaring out from the bottom of the nut. The bearing surface of the flange has serrations which displace material on the mating surface when the nut is wrenched into place, forming a connection to resist loosening.

Product Attributes	
Brand Name	Minerallac Company
Sub Brand	Cully
Туре	Serrated Hex Flange Nut
Special Features	Requires a greater amount of torque to loosen than to tighten the nut. Will span oversized or poorly aligned holes. Does not gall screw threads.
Application	Flange provides a more uniform bearing-stress to clamp-force ratio than other low carbon lock nuts.
Material of Construction	Steel
Finish	Zinc Plated
Nut Type	Lock Nut
Thread Size	20 TPI
Thread Type	Coarse
Thread Direction	Right-Handed
Thickness	0.236" IN
Width	0.438" IN
Size	1/4" IN
Color	Silver
Rockwell Hardness	Rockwell HR15N 78 – 90



Item Status: Active

Standard Qty: 100

Minerallac Company

Tel: 800-927-3293 Fax: 800-824-8942 www.minerallac.com









