

**MECHANICAL CONNECTORS**  
**Aluminum Dual Rated**  
**Tap Connector & Covers**  
**PARALLEL/"T" FORMAT**  
**GP, GC SERIES**



**FEATURES**

- Excellent for tapping of main conductor due to lay-in feature.
- Perpendicular tap allows for parallel or "T" tap configuration.
- Flexible cover allows for either parallel or "T" tap wire entry.
- Secure snap cover eliminates need for taping.
- Electro-tin plated for low contact resistance.

**RATINGS**



**TEMPERATURE RATING:**  
 90 °C.

**VOLTAGE:**  
 600V max.



All dimensional data is listed in inches.

CAT. NO.	FIG. NO.	STYLE
<b>GP-2</b>	1	Parallel "T" Tap
<b>GP-0</b>	1	Parallel "T" Tap
<b>GP-250-0</b>	1	Parallel "T" Tap
<b>GP-250</b>	1	Parallel "T" Tap
<b>GP-350</b>	1	Parallel "T" Tap
<b>GP-500</b>	1	Parallel "T" Tap
<b>GP-750</b>	1	Parallel "T" Tap
<b>GC-2</b>	2	Insulated Covers
<b>GC-0</b>	2	Insulated Covers
<b>GC-250</b>	2	Insulated Covers
<b>GC-350</b>	2	Insulated Covers
<b>GC-500</b>	2	Insulated Covers
<b>GC-750</b>	2	Insulated Covers
<b>GP-2WC</b>	2	Parallel "T" Tap with Cover
<b>GP-0WC</b>	2	Parallel "T" Tap with Cover
<b>GP-250-0WC</b>	2	Parallel "T" Tap with Cover
<b>GP-250WC</b>	2	Parallel "T" Tap with Cover
<b>GP-350WC</b>	2	Parallel "T" Tap with Cover
<b>GP-500WC</b>	2	Parallel "T" Tap with Cover
<b>GP-750WC</b>	2	Parallel "T" Tap with Cover



COLOR CODE	MAIN (RUN) WIRE RANGE	TAP WIRE RANGE	TORQUE VALUE (IN./LBS.)	HEX/WRENCH SIZE	LENGTH (L) (IN.)	WIDTH (W) (IN.)	HEIGHT (H) (IN.)	STD. CTN. QTY.
-	2-12 STR	4-14 STR	50	Slotted	1.390	0.630	0.880	25
-	1/0-2 AWG	1/0-14 AWG	120	0.187	1.750	0.750	1.000	12
-	250 MCM-1/0 AWG	1/0-14 AWG	120 275	0.187, 0.312	2.030	1.060	1.310	12
-	250 MCM-1/0 AWG	250 MCM-6 AWG	275	0.312	2.280	1.060	1.310	12
-	350 MCM-4/0 AWG	350 MCM-6 AWG	275	0.312	2.560	1.250	1.440	6
-	500-350 MCM	500-2 MCM	375	0.375	3.130	1.380	1.750	6
-	750-500 MCM	500-2 MCM	375	0.375	3.380	1.500	2.000	3
Yellow	-	-	-	2.250	1.370	1.110	1.110	12
Gray	-	-	-	2.610	2.170	1.260	1.260	6
Red	-	-	-	3.440	3.180	1.630	1.630	3
Yellow	-	-	-	3.760	3.290	1.760	1.760	3
Blue	-	-	-	4.890	3.340	2.120	2.120	3
Orange	-	-	-	4.550	3.450	2.340	2.340	3
Yellow	2-12 STR	4-14 STR	50	Slotted	2.250	1.370	1.110	12
Gray	1/0-2 AWG	1/0-14 AWG	120	0.187	2.610	2.170	1.260	10
Red	250 MCM-1/0 AWG	1/0-14 AWG	120 275	0.187, 0.312	3.440	3.180	1.630	5
Red	250 MCM-1/0 AWG	250 MCM-6 AWG	275	0.312	3.440	3.180	1.630	5
Yellow	350 MCM-4/0 AWG	350 MCM-6 AWG	275	0.312	3.760	3.290	1.760	6
Blue	500-350 MCM	500-2 MCM	375	0.375	4.890	3.340	2.120	2
Orange	750-500 MCM	500-2 MCM	375	0.375	4.550	3.450	2.340	2

**PARALLEL OR "T" TAP CONNECTORS**

