



WIRE ENTRY PORT
WIRE RANGE: 500KCMIL - #4 AWG
PRE-FILLED W/ OXIDE INHIBITOR

IPL500-3 SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPL500-3	3	3.96
IPL500-4	4	5.11
IPL500-5	5	6.25
IPL500-6	6	7.40
IPL500-7	7	8.59
IPL500-8	8	9.69

CONTACT NSi FOR SALES @ 800.321.5847

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.

		POLARIS SALES CO. INC
PROPRIETARY AND CONFIDENTIAL		11625 PROSPEROUS DRIVE ODESSA, FL 33556
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.		TITLE: INSULATED 500 CONNECTOR
DRAWN BY	NAME	DATE
S.PARRY	S.PARRY	06/2012
MATERIAL: N/A		DWG. NO. IPL500-
SCALE: N/A		SHEET: 1 OF 1