



REMOVABLE CAP  
TO TIGHTEN SCREW  
(REPLACE WHEN COMPLETE)

REMOVABLE CAP  
FOR DUAL ENTRY  
(INSERT IN OTHER SIDE)

IPLD750-5 SHOWN

| PART NUMBER | NO. OF PORTS | LENGTH |
|-------------|--------------|--------|
| IPLD750-3   | 3            | 4.95   |
| IPLD750-4   | 4            | 6.38   |
| IPLD750-5   | 5            | 7.80   |
| IPLD750-6   | 6            | 9.23   |
| IPLD750-7   | 7            | 10.65  |
| IPLD750-8   | 8            | 12.08  |
| IPLD750-10  | 10           | 14.93  |
| IPLD750-12  | 12           | 17.78  |



WIRE ENTRY POINT  
WIRE RANGE: 750KCMIL - 250  
PRE-FILLED W/ OXIDE INHIBITOR

CONTACT NSI FOR SALES @ 800.321.5847

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.

|   |  |  |  |
|---|--|--|--|
|   |  | <b>POLARIS</b><br>SALES CO. INC                        |  |
| PROPRIETARY AND CONFIDENTIAL  |  | 11625 PROSPEROUS DRIVE ODESSA, FL 33556                |  |
| THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED. |  | <b>TITLE:</b><br>INSULATED DUAL ENTRY<br>750 CONNECTOR |  |
| <b>DWG. NO.</b><br>IPLD750-   |  | NAME: _____ DATE: _____                                |  |
| DRAWN BY: S.PARRY 6/2012  |  | MATERIAL: N/A  |  |
| SCALE: N/A  |  | SHEET: 1 OF 1  |  |