

Technical data sheet

Cable fittings and accessories

LUTZE TOP-T Plastic PG



Identification

Type	TOP-T Plastic PG16
Part No.	FPPG16G

Product version

Datasheet version	00
-------------------	----

Use/Application/Properties

Properties	• Integrated strain relief, Wide sealing and clamping range, Easy to install
------------	--

Technical data

Clamping range D	10 mm – 14 mm
Clamping range D	0.394 inch – 0.551 inch
Temperature range	-20 °C ... +100 °C -4 °F ... +212 °F
max. short-time temperature up to	+150 °C / +300 °F
Protection class	IP68
Diameter D	27 mm
Thread form	PG
Thread standard	PG according DIN 40430
Thread G	PG 16
TL	10 mm
TD	22.5 mm
H	31 mm

Construction

Material	PA 6
Material seal	CR chloroprene rubber
Color	grey RAL 7001

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

Technical data sheet

Cable fittings and accessories

Certifications/Standards

Certifications cULus

Notes and Comments

Note Locknuts sold separately

Dimensions

