

PLENUM CONTROL CABLE

OMNIPLÉN
200C FEP -300 Volt
UL Rated

CONSTRUCTION	
Conductor	- Stranded tinned copper
Insulation	- Color coded FEP
Shield	- Aluminum / Mylar shield with tinned copper drain Wire
Jacket	- Color Coded FEP, (Red jacket available for Alarm Cable, use -03)

Applications:

- Audio and control cable
- Alarm and signal use
- Oil and gasoline resistant

Standards:

- UL Rated
- CL3P Rated
- CMP Rated

Part #	AWG	Conductors	Stranding	Insulation Thickness	Jacket Thickness	Nom. O.D.	Lbs./M'
G12202	22	2	7 x 30	.007"	.010"	.108"	12
G12204	22	4	7 x 30	.008"	.010"	.125"	18.8
G12206	22	6	7 x 30	.008"	.010"	.150"	23
G12208	22	8	7 x 30	.010"	.010"	.192"	30
G12212	22	12	7 x 30	.010"	.010"	.198"	41
G12215	22	15	7 x 30	.010"	.010"	.221"	50
G12225	22	25	7 x 30	.010"	.010"	.280"	81
G12002	20	2	7 x 28	.009"	.010"	.124"	16
G12003	20	3	7 x 28	.009"	.010"	.131"	21
G11802	18	2	7 x 26	.006"	.010"	.132"	20
G11802-03	18	2	19/30	.007"	.016"	.165"	23.2
G11803	18	3	7 x 26	.008"	.010"	.153"	27
G11804	18	4	7 x 26	.008"	.010"	.167"	33.7
G11806	18	6	7 x 26	.010"	.010"	.204"	49
G11808	18	8	7 x 26	.010"	.010"	.264"	63
G11810	18	10	7 x 26	.010"	.010"	.264"	75
G11815	18	15	7 x 26	.010"	.010"	.310"	110
G11602	16	2	19 x .0117	.008"	.010"	.162"	31.9
G11603	16	3	19 x .0117	.008"	.010"	.172"	42.2
G11604	16	4	19 x .0117	.008"	.010"	.190"	52.9
G11402	14	2	19 x .0185	.008"	.010"	.182"	42
G11404	14	4	19 x .0147	.008"	.010"	.214"	68
G11202	12	2	19 x .0185	.008"	.010"	.216"	64

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.*G1xxxx-03 is Red Alarm Cable

COLOR CODE CHART

Cond. #	Color
1	Black
2	Red
3	White
4	Green
5	Brown
6	Blue
7	Orange
8	Yellow
9	Purple
10	Gray
11	Pink
12	Tan
13	Red/Black Stripe
14	White/Black Stripe
15	Green/Black Stripe
16	Blue/Black Stripe
17	Orange/Black Stripe
18	Yellow/Black Stripe
19	Purple/Black Stripe
20	Gray/Black Stripe
21	Pink/Black Stripe
22	Tan/Black Stripe
23	Black/White Stripe
24	Red/White Stripe
25	Green/White Stripe