

PLENUM CONTROL CABLE

Nonshielded Conductors
OMNIPL



CONSTRUCTION	
Conductor	- Stranded Bare copper
Insulation	- OMNIPL
Shield	- None
Jacket	- OMNIPL

Applications:

- Power limited control circuits
- Wiring of the following systems:
 - -Intercom
 - -Security
 - -Audio
- Suggested Voltage Rating: 300 Volts

Standards:

- NEC Article 725-CL3P, CMP, MPP

Part #	AWG	Conductors	Insulation Thickness	Jacket Thickness	Nom. O.D.	Lbs./M'
G122202	22	2	.006"	.010"	.104"	8
G122203	22	3	.006"	.010"	.110"	11
G122204	22	4	.006"	.010"	.121"	14
G122206	22	6	.006"	.010"	.146"	21.8
G122208	22	8	.006"	.010"	.188"	27
G122210	22	10	.006"	.010"	.203"	33
G122212	22	12	.006"	.010"	.218"	39.6
G122002	20	2	.006"	.010"	.120"	12.3
G122002-BW	20	2	.006"	.010"	.120"	12
G122003	20	3	.006"	.010"	.127"	17
G122004	20	4	.006"	.010"	.140"	22

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

COLOR CODE CHART

Cond. #	Color
1	Black
2	Red
3	White
4	Green
5	Brown
6	Blue
7	Orange
8	Yellow
9	Purple
10	Gray
11	Pink
12	Tan