

DATA / VOICE CABLE

Cat5e -Category -5E
CMR, 350 MHz



CONSTRUCTION	
Conductor	- Solid annealed bare copper
Insulation	- Polyethylene
Shield	- Aluminum foil
Drain Wire	- Mylar tape with tinned copper drain wire
Jacket	- Flame retardant PVC
Ripcord	- Yes

Applications:

- ATM 155 Mbps
- Ethernet 10BASET, 100BASETX, 100BASEVG, 100BASET4
- 1000 Mbps 1000BASET Gigabit Ethernet (IEEE 802.3)
- 16 Mbps Token Ring (IEEE 802.5)

Standards:

- ETL/UL Available
- ROHS Compliant

Part #	AWG	Pairs	Nom. O.D.	Lbs./M'	Jacket Color
J262404-DB	24	4	.310"	49	Black
J262404-XX	24	4	.2244"	22	

Note: The information in this specification sheet is approximate and subject to standard industry and manufacturer tolerances. Please verify specific requirements with your Omni Cable account manager.

Insert the color number in the -XX location:

- 01 = Black
- 02 = White
- 03 = Red
- 04 = Green
- 05 = Blue
- 07 = Orange
- 08 = Yellow
- 09 = Purple
- 11 = Pink