




PANDUIT P/N	WEIGHT
FST24H3	.2 LB/EA 90 g/EACH

NOTES:

1. SEE CATALOG FOR COMPLETE LIST OF PARTS APPLICABLE FOR USE WITH THIS PRODUCT.
2. DIMENSIONS IN PARENTHESIS ARE METRIC.
3. SPLICE TRAY HOLDER WILL ACCOMMODATE UP TO (3) FST24 SPLICE TRAYS.
4. SPLICE TRAY HOLDER IS SUPPLIED WITH 1 TY-TAK AND 4 PUSH FASTENERS
5. MATERIAL- ALUMINUM



MODEL FILENAME	V10049FN_FST24H3_ASSY_01.prt
CAD FILENAME/LAYERS	V10049FN_DC_01A.prt (1)

PANDUIT CORP. TINLEY PARK, ILLINOIS

SPLICE TRAY HOLDER
(FST24H3)
CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(.X) ± .03 (.XXX) ± .005
(.XX) ± .015 ANGLES ± 1°

UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE GIVEN
IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY
JDWE

DATE	5-3-07
------	--------

CHK'D	
-------	--

MAT'L:

SEE NOTES

SCALE	NONE
-------	------

DRAFTING NO.

10049-59

020

SIZE

01	5-10-02	RYB		A. ADD .24 DIA HOLE; B. ADD .15 X .35 SLOTS (2X);	10049-59					
R	5-2-02	JDWE		RELEASED TO PRODUCTION	10049-59					
REV	DATE	BY	CHK	DESCRIPTION	ECN	R	CUST	SUP	OTH	