


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

|                                                |                                                                                                                                                |
|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                                       | High Conductivity Seamless Copper Tube                                                                                                         |
| Plating                                        | Electro-Tin                                                                                                                                    |
| Wire Size                                      | 3/0 STR/FLEX                                                                                                                                   |
| Wire Type                                      | Stranded Copper: Class B & C, Compact, Class G, H, I, K, M, Locomotive                                                                         |
| Wire Strip Length                              | 1.0 in.                                                                                                                                        |
| Stud Size                                      | 5/8 in.                                                                                                                                        |
| UL Listed Wire Connector                       | Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts. |
| UL Temperature Rating                          | 90° C                                                                                                                                          |
| C.S.A Certified Wire Connector                 | Yes                                                                                                                                            |
| Panduit Color Code on Barrel                   | ORANGE                                                                                                                                         |
| Panduit Die Index No. on Barrel                | P50                                                                                                                                            |
| Alternate Industry Die Index No. ( ) on Barrel | (14)                                                                                                                                           |



| 01  | 7/10 | JHNU | JHNU | TONGUE WIDTH WAS 1.19, THICKNESS WAS .16 |     |
|-----|------|------|------|------------------------------------------|-----|
| REV | DATE | BY   | CHK  | DESCRIPTION                              | ECN |

**PANDUIT CORP. TINLEY PARK, ILLINOIS**

LCAX3/0-58-X  
Copper Lug - One-Hole, Standard Flex Barrel

SCALE N/A DRAWING NO / CAD FILE LCAX3\_0-58-CUST