Pioling Bechto-Tin Wrie Size 3/0 AWG Wrie Type Stranded Copper, Class B: Concentric, Class C: Concentric Wrie Strip Length 1-//16 in. Stud Size 1/2 In. UL Usided Wire Connector Yes, for applications up to 3Sky. Connector UL Uside Wire Connector Yes, for applications genetier mann 2000 volts. UL Temperature on Barnel 90° C C.S.A Certified on Barnel Yes Pronduit Color Code on Barnel ORANGE Jeb Index No. P50 Jeb Index No. Size0 Jeb Index No. P50 Jeb Index No. Size0 Jeb Index No. Size0 Jeb Index No. Copper Lug Two-Holes, Long Barrel Jeb Index No. Ize0 Jeb Index No. Ize0 Jeb Index No.	Material		A RESTRICTED BASIS AND IS NOT TO BE L High Conductivity Seamless Copper Tube			ERESTS OF FANDUT CORF.
Wire Type Stranded Copper: Class B: Concertific, Class C: Concentric Original Stranded Copper: Class B: Concentric, Class C: Concentric Vire Strip Length 1-9/16 in. Stud Size 1/2 in. UL Listed Wire Connector Ves. for opplications up to 35k. Voltage stress relief instructions with applications greater than 2000 volts.	Plating		Electro-Tin			
Interview Compact: Compact: Compact: Comparised or incomplexest	Wire Size		3/0 AWG			63 R Ref
UL Listed Wire Connector Yes, for applications up to 35k. Consult cable manufacturer for voltage stress refiel instructions with applications greater than UL Temperature Rating 90° C C.S.A Certified Wire Connector Yes Panduit Color Code on Borrel ORANGE Attemate Industry Die Index No. [] on Barrel P50 Attemate Industry Die Index No. [] on Barrel [14] Attemate Industry Die Index No. [] on Barrel [14] .13±.01 .13±.01 CERTIFIED USEED Wire Connector .13±.01 .13±.01	Wire Type		Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric			barrel markings
UL Listed Wire Connector Yes, for applications up to 35k. Consult cable manufacturer for voltage stress refiel instructions with applications greater than UL Temperature Rating 90° C C.S.A Certified Wire Connector Yes Panduit Color Code on Borrel ORANGE Attemate Industry Die Index No. [] on Barrel P50 Attemate Industry Die Index No. [] on Barrel [14] Attemate Industry Die Index No. [] on Barrel [14] .13±.01 .13±.01 CERTIFIED USEED Wire Connector .13±.01 .13±.01	Wire Strip Length	า	1-9/16 in.	.96±.04	4150 STR C 33/0-1	
Connector Consult coble manufacturer for with opplications greater than 200 volts. UL Temperature 70° C C.S.A Certified Wire Connector Yes Pandult Color Code ORANGE Pandult Color Code ORANGE Pandult Die Index No. (1) on Barrel OFSO Alternate Industry (14) Die Index No. (1) OR Barrel OFSO LISTED ULSTED OR CONNECTOR LISTED ULSTED OR CONNECTOR CERTIFIED VIE COnnector	Stud Size		1/2 in.		3/0 LCC0	
UL lemperature 90° C Refing C.S.A Certified Yes Ponduit Color Code ORANGE Panduit Die Index No. 0 on Barrel Alternate Industry Die Index No. () on Barrel Alternate Industry Die Index No. () on Barrel .13±.01			Consult cable manufacturer for voltage stress relief instructions with applications areater than	.63±.04 1	.75±.02 —	(2) PLS
Wire Connector Panduit Color Code on Barrel ORANGE Panduit Die Index No. on Barrel P50 Alternate Industry Die Index No. () on Barrel (14) User CERTIFIED User Connector .13±.01 .13±.01 .13±.01 .13±.01 LISTED Wire Connector .13±.01 .13±.01 .13±.01 .13±.01 .13±.01 .13±.01 .13±.01 .13±.01 .13±.01 .13±.01 .13±.01 .13±.01 .13±.01			90° C			5.03±.06
on Barrel Panduit Die Index No. () Alternate Industry Die Index No. () On Barrel Image: Cerrified Wire Connector Image: Discover of the	C.S.A Certified Wire Connector		Yes			
on Barrel Alternate Industry (14) Die Index No. (1) (14) On Barrel .13±.01 USE .13±.01			ORANGE			
Die Index No. (1) .51±01 .64±01 Image: CERTIFIED Connector .13±.01 .13±.01	Panduit Die Index No. on Barrel		P50]		
CERTIFIED LISTED Wire Connector	Die Index No. ()		(14)			.51±.01 .64±.01
Image: Constraint of the second se	CE	ERTIFIEL	d listed	±.01		
Image: Constraint of the second se						CORP. TINLEY PARK, ILLINOIS
						LCC3/0-12-X
					SCALE DRAWING NO / CAD FILE	