



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	6 AWG
Wire Type	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric
Wire Strip Length	7/8 in.
Stud Size	1/4 in.
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90° C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	BLUE
Panduit Die Index No. on Barrel	P24
Alternate Industry Die Index No. () on Barrel	(7)



LISTED Wire Connector



REV	DATE	BY	CHK	DESCRIPTION	ECN	-R	SUP	SCALE
02	6/19	JHNU	JHNU	MOVED PANDUIT & UL/CSA LOGOS ON STAMP	N10884RY-LCD6-14A-CUST	RGB	RGB	N/A
01	11/03	DRL	DRL	REMOVED NAVY NUMBER FROM STAMP, MOVED PANDUIT, UL & CSA	11322			

PANDUIT CORP. TINLEY PARK, ILLINOIS

LCD6-14A-L
Copper Lug - Two-Hole, Standard Barrel

DRAWING NO / CAD FILE
LCD6-14A-CUST