



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



CID\*\*-C, PHONE OR DATA ICON LOCATED HERE, IDENTIFIES INDIVIDUAL PORT. OPTIONAL, NOT SUPPLIED.

PANDUIT PART NO.	WEIGHT (APPOX.)
NK5EPPG48Y	2.2 lb (997.9 g)

NOTES:

- MATERIAL:  
 PANEL HOUSING: STEEL  
 RJ45 MODULES: THERMOPLASTIC RESIN UL94V-0  
 PUNCHDOWN BLOCKS: THERMOPLASTIC RESIN UL94V-0  
 BEZEL ASSEMBLY: THERMOPLASTIC RESIN UL94H-B  
 RETENTION CAP: THERMOPLASTIC RESIN UL94V-0
- 48 PORT PATCH PANEL 8 POSITION 8 WIRE.
- THE PATCH PANEL IS DESIGNED FOR MOUNTING TO 19" UNIVERSAL RACKS.
- FOUR (4) 12-24 X 1/2" ROUND HEAD SCREWS ARE PROVIDED FOR FASTENING TO RACKS.
- DIMENSIONS IN BRACKETS ARE IN METRIC.
- USE 110 STYLE TERMINATION TOOL FOR PUNCHDOWN.
- RETENTION CAPS (ONE PER CONNECTOR) PROVIDED FOR SNAP-IN ON TERMINATED CONNECTORS.

PART NUMBER		NK5EPPG48Y	
TITLE		NETKEY CAT5E 48 PORT PATCH PANEL	
		CUSTOMER DRAWING	
ITEM REVISION NAME		M02479JM/01	
DATASET FILE NAME		M02479JM_DC249_01A	
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [ mm ]		MATERIAL:	
.x ± .xxx ± .010 [ .3 ]		SEE NOTE 1	
.xx ± .03 [ .8 ] ANGLES ±		DRAWING NUMBER:	
THIRD ANGLE PROJECTION		02479-249	
DRAWN BY	DATE	CHK	SCALE
LZ	3-4-06	CEF	.25-1
SHT 1 OF 1		A	

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
2	9-27-18	BAME	KRKE	MMR	B. REMOVED M6 SCREWS	M09000HW
1	5-13-14	MDJR	REFR	JCK	A. UPDATED TITLE BLOCK	02479-249
R	3-4-06	LZ	CEF	CEF	RELEASED TO PRODUCTION	02479-249

D101000DA/14