

Products

- > [Index](#)
- > [Featured Products](#)
- > [Cross Reference](#)
- > [UPC Search](#)

**Product Datasheet**

[Catalog Home](#) [Home Page](#)

[Search](#)

## 3443 -- 45 Degree Liquidtight Connector 3/4" Trade Size



**Product Specifications**

<b>Family</b>	Liquidtight Conduit and Cord Connectors
<b>Fittings Classification</b>	Malleable Iron - 45 Degree Connectors
<b>Sub Class</b>	Uninsulated
<b>Trade Size</b>	3/4"
<b>Standard Packaging</b>	Carton
<b>Ship Carton Length</b>	7.3750
<b>Ship Carton Width</b>	5.6250
<b>Ship Carton Height</b>	4.1875
<b>WT. PER HU.</b>	34.80
<b>Dimension A</b>	1-5/8"
<b>Dimension B</b>	19/32"
<b>Thread Spec. B</b>	3/4-14 NPT
<b>Dimension C</b>	2-13/16"
<b>Dimension D</b>	1-3/16"
<b>Unit Carton Quantity</b>	25
<b>Ship Carton Quantity</b>	25
<b>UPC Number</b>	050169034439

**Applications**

- For use in outdoor or indoor locations on flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Use to positively bond the conduit to a box or enclosure
- RACO® liquidtight connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

### Product Features

- Patented split gland-ring is designed to slip onto the conduit quickly and to grip the jacket of the conduit, speeding installation, assuring a perfect seal, and preventing pullouts
- Malleable iron castings mate with other components perfectly without strain or distortion
- All components are reusable -- RACO® liquidtight connectors may be easily disassembled and reused after years of service
- Sealing washer (included) provides a liquidtight seal when terminating the connector in a threadless opening
- Heavy duty locknut included with every RACO® liquidtight connector assures continuity of ground
- All metallic components are zinc electro plated for added corrosion protection

### Compliances

UL CSA

