

Model # 22070T

# 1000A AC/DC TRUE RMS CLAMP METER

1000A AC/DC clamp meter combines the features needed for the professional electrician including True RMS readings, a built-in non-contact AC voltage detector, and Multimeter, Capacitance and Temperature functions.



**NON-CONTACT VOLTAGE TESTER**  
Built-in non-contact AC voltage detector

**TRUE RMS**  
For accurate measurements of non-linear loads

**VERSATILE**  
Measures both AC and DC Current

**MULTI FUNCTION**  
Capacitance, Frequency, Duty Cycle, and Temperature functions

**MAX/MIN/RECORD**  
Captures current fluctuations

**RUGGED DESIGN**  
Impact resistant double molded housing provides comfortable grip

**EASY TO READ DISPLAY**  
Backlit 6000-count digital display with bargraph

- 12 FUNCTIONS**
- AC Current
  - DC Current
  - AC Voltage
  - DC Voltage
  - Non-contact AC Voltage
  - Resistance
  - Capacitance
  - Frequency
  - Duty Cycle
  - Temperature
  - Continuity
  - Diode Test



southwiretools.com

BUILT FOR DURABILITY. BUILT FOR RELIABILITY.  
**BUILT FOR WORK.**



Southwire™

**Model # 22070T**

**1000A AC/DC TRUE RMS CLAMP METER**

## FEATURES


- **True RMS** for accurate measurements of non-linear loads such as motordrives, florescent lights, and lamp dimmers
- Easy to read backlit digital display with bargraph – great for low light work environments
- Capacitance, Frequency, Duty Cycle and Temperature functions
- Built-in non-contact AC voltage detector
- Impact resistant double molded housing provides comfortable grip
- High accuracy measurements of both AC and DC Current

- 22070T Clamp meter
- Test leads
- Type K temperature probe with banana plug adapter
- Carrying case
- 9 volt battery

## INCLUDES

## SPECIFICATIONS

| 1000A True RMS AC/DC Clamp Meter (22070T) |                                      |                 |                               |
|-------------------------------------------|--------------------------------------|-----------------|-------------------------------|
|                                           | Range                                | Max. Resolution | Basic Accuracy (% of reading) |
| AC Current:                               | 1000A                                | 0.1A            | ±2.8%                         |
| DC Current:                               | 1000A                                | 0.1A            | ±2.8%                         |
| Jaw Opening:                              | 1.57" (40mm)                         |                 |                               |
| AC Voltage:                               | 600V                                 | 0.001V          | ±1.8%                         |
| DC Voltage:                               | 600V                                 | 0.1mV           | ±0.8%                         |
| NCV:<br>(non-contact AC voltage)          | 100 to 600V                          | -               | -                             |
| Resistance:                               | 60MΩ                                 | 0.1Ω            | ±1.5%                         |
| Capacitance:                              | 4000μF                               | 0.01nF          | ±3.0%                         |
| Frequency:                                | 10kHz                                | 10Hz            | ±1.5%                         |
| Duty Cycle:                               | 99%                                  | 0.5%            | ±1.2%                         |
| Temperature:                              | -4 to 1400°F<br>-20 to 760°C         | 0.1°F<br>0.1°C  | ±3.0%                         |
| Continuity:                               | Audible threshold: Approximately 30Ω |                 |                               |
| Diode Test:                               | Yes                                  |                 |                               |
| Dimensions:                               | 9.06 x 2.99 x 1.58 in.               |                 |                               |
| Weight:                                   | 610g                                 |                 |                               |



**Southwire Company**  
**One Southwire Drive**  
**Carrollton, GA 30119**



**Southwire™**



**Customer Service: 1-855-SWTOOLS (855-798-6657)**

Scan code to see more  
Southwire Tools

**southwiretools.com**