

Compression Connectors for Copper Conductor


Two-Hole Lugs — Long Barrel 600V to 35KV (continued)

Material: High-Conductivity
Wrought Copper

Finish: Electro Tin Plate



Peep Holes Available!
Add suffix **-PH**



CAT. NO.	WIRE SIZE				DIMENSIONS (IN.)								DIE CODE	DIE COLOR
	CODE	FLEX CLASS G, H, I, K, M†	BOLT SIZE		A	B	C	D	E	F	H			
54814BE			¼		2.62	1.25	.83	.13	.57	¼	¾		45	BLACK
256-30695-1299		125 Navy	¼		2.69	1.31	.81	.13	.57	¼	¾		45	
256-30695-1116	2/0 AWG	275/24 = 111 kcmil	¾		3.19	1.81	.83	.13	.57	¾	1		45	
256-30695-1116P		1/0 Weld	¾		3.19	1.81	.83	.13	.57	¾	1		45	
54862BE*			½		4.20	2.81	.83	.13	.57	½	1¾		45	
54815BE		2/0 Weld	¼		2.89	1.45	.92	.13	.63	¼	¾		50	ORANGE
54816BE	3/0 AWG	325/24 = 131 kcmil	¾		3.25	1.63	.92	.13	.63	¾	1		50	
54864BE		150 Navy	½		4.48	3.00	.94	.13	.63	½	1¾		50	
54817BE			¼		3.15	1.38	1.03	.14	.70	¼	¾		54	PURPLE
54818BE		200 Navy	¾		4.38	2.63	1.03	.14	.70	¾	1¾		54	
256-30695-1117	4/0 AWG	450/24 = 182 kcmil	¾		3.35	1.81	1.03	.14	.70	¾	1		54	
256-30695-1117P		3/0 Weld	¾		3.50	1.88	1.03	.14	.70	¾	1		54	
54866BE*			½		4.70	3.00	1.03	.14	.70	½	1¾		54	
256-30695-1245		250 Navy	¾		3.83	1.93	1.13	.14	.77	¾	1		62	YELLOW
256-30695-1245P	250 kcmil	550/24 = 222 kcmil,	¾		3.83	1.93	1.13	.14	.77	¾	1		62	
54868BE*		4/0 Weld	½		4.92	3.00	1.13	.14	.77	½	1¾		62	
54819BE	300 kcmil	300 Navy	¾		5.04	2.80	1.25	.15	.85	¾	1		66	WHITE
54870BE		250 Weld, 262, 650/24	½		5.23	3.00	1.25	.15	.85	½	1¾		66	
54820BE			¼		4.29	1.93	1.36	.18	.93	¼	¾		71	RED
256-30695-1118	350 kcmil		¾		4.33	1.93	1.36	.18	.93	¾	1		71	
256-30695-1118P			¾		4.33	1.93	1.36	.18	.93	¾	1		71	
54872BE			½		5.40	3.00	1.36	.18	.93	½	1¾		71	
54822BE		400 Navy	¼		4.38	1.93	1.41	.17	.96	¼	¾		76	
54821BE	400 kcmil	775/24 = 313 kcmil	¾		4.43	1.93	1.41	.17	.96	¾	1		76	BLUE
54874BE		300 Flex, 350, 259 Str.	½		5.51	3.00	1.41	.17	.96	½	1¾		76	
54823BE			¼		4.93	1.94	1.61	.22	1.10	¼	¾		87	BROWN
256-30695-1119	500 kcmil	400 Weld, G, H, I	¾		5.00	1.93	1.61	.22	1.10	¾	1		87	
256-30695-1119P		925/24 = 373 kcmil	¾		5.00	1.93	1.61	.22	1.10	¾	1		87	
54876BE		350, K	½		6.00	3.00	1.61	.22	1.10	½	1¾		87	
54824BE	600 kcmil	450, I, K	¾		5.70	2.80	1.75	.24	1.20	¾	1		94	
54878BE		1100/24 = 444 kcmil	½		5.83	3.00	1.75	.24	1.20	½	1¾		94	GREEN
54879BE	700 kcmil	1325/24 = 535 kcmil	½		5.83	3.00	1.80	.24	1.25	½	1¾		99	
256-30695-1222			¾		5.25	2.06	1.94	.27	1.33	½	1		106	BLACK
256-30695-1222P	750 kcmil	500, G, H, I, K	¾		5.25	2.06	1.94	.27	1.33	½	1		106	
54880BE		1325/24 = 535 kcmil	½		6.20	3.00	1.94	.27	1.33	½	1¾		106	
58884BE		1600/24 = 646 kcmil	½		6.16	3.00	1.94	.27	1.33	½	1¾		106	
58826BE	900 kcmil	1925/24 = 777 kcmil	½		6.74	3.00	2.18	.31	1.50	½	1¾		115	
54826BE	1000 kcmil	1000 Navy	¾		6.49	2.80	2.27	.30	1.55	¾	1		125	N/A
54882BE			½		6.66	3.00	2.27	.30	1.55	¾	1¾		125	
54888BE	1250 kcmil	929, 2300/24	½		7.88	3.00	2.42	.35	1.67	¾	1¾		140	

† Contact Technical Services for specific stranding listings

* UL® Listed for direct-burial applications

Tooling: pp. F-80-F-100 Die Selector Chart: pp. F-101-F-104

www.tnb.com

United States
Tel: 901.252.8000
800.816.7809
Fax: 901.252.1354

Technical Services
Tel: 888.862.3289

Thomas & Betts