

# **Steel City**® Hangers & Clamps

## Conduit Hangers, Strut Accessories, Hardware


Pages 89-96




Page 90




Page 90




Page 90



Page 90



Page 91




Page 91



Page 92



Page 92




Page 92



Page 93




Page 93




Page 94




Page 95




Page 95




Page 96



Page 96



Page 96




Page 96



Page 96

# Steel City® Hangers & Clamps

## Conduit Hangers



### Features

- Accommodates 1/2" through 4" EMT or rigid conduit.
- Can be used for either vertical or horizontal installation.
- 6HTB Series with thread impression so there are less parts to handle or drop.
- Installs easily with a screwdriver.



Fig. 1



Fig. 2



Fig. 3

## 6H Series Conduit and Pipe Hangers

With Bolt		Without Bolt		EMT	Rigid Conduit or Pipe	Qty. per Box
Cat. No.	Fig. No.	Cat. No.	Fig. No.			
6H0-B	2	6H0	1	1/2	3/8-1/2	100
6H0-TB	3	6H0	1	1/2	3/8-1/2	100
6H1-B	2	6H1	1	3/4	3/4	100
6H1-TB	3	6H1	1	3/4	3/4	100
6H2-B	2	6H2	1	1	1	100
6H2-TB	3	—	—	1	1	100
6H2 1/2-B	2	6H2 1/2	1	1-1/4	—	100
6H2 1/2-TB	3	—	—	1-1/4	—	100
6H3-B	2	6H3-SC	1	1-1/2	1-1/4	100
6H3-TB	3	—	—	1-1/2	1-1/4	100
6H4-B	2	6H4	1	—	1-1/2	100
6H4-TB	3	—	—	—	1-1/2	100
6H5-B	2	6H5	1	2	2	100
6H5-TB	3	—	—	2	2	100
6H6-B	2	6H6	1	2-1/2	2-1/2	100
6H7-B	2	6H7	1	3	3	100
6H8-B	2	6H8	1	3-1/2	3-1/2	100
6H9-B	2	6H9*	1	4	4	100

\* CSA not applicable

Add **SS** suffix to part number for stainless steel.

Load rating is 500 lbs. with a safety factor of 3. Available with or without closure bolt.

Standard finishes: electrogalvanized and Type 302 Stainless Steel.

Top hole diameter : 6H0 to 6H3 = 9/32"  
6H4 to 6H9 = 11/32"



### Features

- Supports threaded rod, threaded bridle rings and electrical boxes.
- Bright zinc plating.
- Supports 100 lbs. static load limit.





Fig. 1




Fig. 2

### Beam Clamps—Malleable Iron, Electroplated Finish

Catalog Number	Fig. No.	Description	Static Load Limit	Pkg. Per Box
BC1-TB*	1	Steel beam clamp, 1/4"-20 threaded openings, fits flanges up to 5/8" thick	75	50
BC2-TB*	1	Steel beam clamp, 5/16"-18 threaded openings, fits flanges up to 3/4" thick	320	50
510	2	Malleable iron beam clamp, 1/4"-20 threaded openings, fits flanges up to 5/8" thick	400	100
511-SC	2	Malleable iron beam clamp, #10-24 threaded openings, fits flanges up to 5/8" thick	400	100
500-SC	2	Malleable iron beam clamp, 1/4"-20 threaded openings, fits flanges up to 15/16" thick	450	100
509	2	Malleable iron beam clamp, #10-24 threaded openings, fits flanges up to 15/16" thick	375	100
501	2	Malleable iron beam clamp, 15/16"-18 threaded openings, fits flanges up to 7/8" thick	800	100
502	2	Malleable iron beam clamp, 3/8"-16 threaded openings, fits flanges up to 1" thick	1300	100
503-SC	2	Malleable iron beam clamp, 1/2"-13 threaded openings, fits flanges up to 1" thick	1300	100
507	2	Malleable iron beam clamp, 1/2"-13 threaded openings, fits flanges up to 1-3/8" thick	1700	100
508	2	Malleable iron beam clamp, 1/2"-13 threaded openings, fits flanges up to 2-1/8" thick	1700	100

Safety Factor of 3. Load Ratings based on bottom hole of Beam Clamp.

\* CSA not applicable



# Steel City® Hangers & Clamps

## Conduit Hangers




Fig. 1



Fig. 2




Fig. 3

## Beam Clamps

Cat. No.	Fig. No.	Dimension in Inches		Qty. per box
		O.D. of Conduit or Pipe	Nom. Conduit or Pipe Size	
<b>RCS Clamp-Steel</b>				
RCS-1/2	1	.840	1/2	50
RCS-3/4	1	1.050	3/4	50
RCS-1	1	1.315	1	100
RCS-1-1/4	1	1.660	1-1/4	100
RCS-1-1/2	1	1.900	2	100
RCS-2	1	2.375	2	100
<b>RC Clamp-Malleable Iron</b>				
RC-3/8	1	.675	3/8	50
RC-1/2	1	.840	1/2	50
RC-3/4	1	1.050	3/4	50
RC-1	1	1.315	1	100
RC-1-1/4	1	1.660	1-1/4	100
RC-1-1/2	1	1.900	1-1/2	100
RC-2-SC	1	2.375	2	100
RC-2-1/2	1	2.875	2-1/2	100
RC-3	1	3.500	3	100
RC-3-1/2	1	4.000	3-1/2	100
RC-4-SC	1	4.500	4	100
<b>EC Clamp-Malleable Iron</b>				
EC-1/2	2	.840	1/2	50
EC-3/4	2	1.050	3/4	50
EC-1	2	1.315	1	100
EC-1-1/4	2	1.660	1-1/4	100
EC-1-1/2	2	1.900	1-1/2	100
EC-2	2	2.375	2	100
EC-2-1/2	2	2.875	2-1/2	100
EC-3	2	3.500	3	100
<b>PC Clamp-Malleable Iron</b>				
PC-3/8	3	.675	3/8	50
PC-1/2	3	.840	1/2	50
PC-3/4	3	1.050	3/4	50
PC-1	3	1.315	1	100
PC-1-1/4	3	1.660	1-1/4	100
PC-1-1/2	3	1.900	1-1/2	100
PC-2	3	2.375	2	100
PC-2-1/2	3	2.875	2-1/2	100
PC-3	3	3.500	3	100
PC-3-1/2	3	4.000	3-1/2	100
PC-4	3	4.500	4	100

