

Flexible Conduits & Fittings T&B Catalog Number:

BVND-N043GT

UPC Number: 78620995126 Status: Active

Description:

PMAFIX straight black connector with NPT threads and universal safety clip. Material - polyamide 6, thread size - 3/4 in., conduit size NW - 23.

Ann	lica	tion

• •	
	For cable protection systems in a wide range of applications
Characteristics	
	Vary high impact registance
	Very high impact resistance
	Vibration proof connection to PMAFLEX conduits
	High conduit pull-out strength
	Very good chemical properties Free from halogens and cadmium
	Fits both conduit profiles - Fine (T) and coarse (G)
	Easy installation, simply push the conduit in
	Can be easily re-opened with a screwdriver
General	Can be easily re-opened with a screwdiver
Material	Polyamide 6
Color	Black
Thread Type	NPT
Compatiable With	PMAFLEX, PMA Smart Line
Dimension Information	
Fits to Conduit Size (NW)	23
Fits to Conduit Size (metric)	25
Fits to Conduit Size (inches)	3/4
Thread Size (NPT)	3/4
Technical Information	
Temperature Range-Continuous (Celsius) -40 degree C to +105 degree C
Temperature-Short-Term (Celsius)	+160 degree C
Technical Data Sheet	Available on Website
Chemical Resistance Chart	Available on Website
Specifications	
3dmodel	Available on Website
IP Ratings	Tivaliable of Wester
IP Rating	IP66 stat. / IP54 dyn.
Packaging	ir oo stat. / ir 54 dyll.
	•
T&B Inner Pack	30
Package in Units	210
T&B Sold in UOM	Each
T&B Weight Per UOM Application Support	4.5 lbs. per 100
Application Support	
PMA Reference Guide	Available on Website
Prouduct Overview-PMAFIX Connectors	Available on Website
PMAFIX Connectors-Safety and Sealing Systems	Available on Website



Certifications

RoHS Compliance

Yes

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com