



Representative

**Catalog Number:** DJ4X1C-2000  
**Product ID:** 7TAA241030R0086  
**UPC Number:** 03448117837  
**Status:** Active

Riser-Gard Fiber Optic Corrugated Conduit, Size 2 Inches, Outer Diameter 2.38 Inches, Inner Diameter 2 Inches, Wall Thickness 0.080 Inch, Length 2,000 Feet, Material PVC, Color White, with Pull Tape

### North American Specifications (UNSPSC)

|                  |   |
|------------------|---|
| UNSPSC           | 39131706 Electrical conduit   |
| IGCC             | 5535 Electrical conduit   |
| Brand Name       | Carlton   |
| Type             | Riser-Gard Flexible Raceway   |
| Special Features | UL Listed and is available with tape pre-installed.   |
| Application      | Riser-Gard is suitable for use in vertical runs in a shaft or between floors, as well as areas other than the plenum. |
| Standard         | UL e151168  |
| Trade Size       | 2 Inches  |
| Outside Diameter | 2.38 Inches   |
| Inside Diameter  | 2 Inches  |
| Length           | 2,000 ft  |
| Material         | PVC   |
| Color            | Orange  |

### European Specifications (ETIM)

|  |                                  |
|--|----------------------------------|
| ETIM                                       | EC001175 Corrugated plastic hose |
| Nominal diameter                           | 50.8mm                           |
| Nominal size in inch                       | 2 inch                           |
| Outer diameter                             | 60.3mm                           |
| Inner diameter                             | 50.8mm                           |
| Material                                   | PVC                              |
| Operating temperature                      | -20 - +40°C                      |
| UV resistant                               | N                                |
| Colour                                     | Orange                           |
| Sheathing material                         | Not sheathed                     |
| Approved according to DIN EN 61386-23      | N                                |
| Approved according to UR                   | N                                |
| Approved according to LUL/British Standard | N                                |
| Approved according to Lloyd's Register TA  | N                                |
| Approved according to UTAC                 | N                                |
| Approved according to DIN 5510             | N                                |
| Approved according to NF F 16-101          | N                                |

### Packaging

|                           |                |
|---------------------------|----------------|
| Outer Quantity            | 2000           |
| Outer Dimensions (inches) | 1x1x1          |
| Weight Uom                | 0.45 lbs. Each |

### Documents / Support Tools

|                                       |                      |
|---------------------------------------|----------------------|
| Technical Drawing / Data Sheet        | WSD-AC04182          |
| Technical Drawing / Data Sheet Canada | Available on Website |

For further technical assistance, please contact us...

ABB Installation Products - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

ABB Installation Products Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)