

Actual

Catalog Number: DTW516

 Product ID:
 7TAH007050R0017

 UPC Number:
 78621086844

 EAN Number:
 05414363150305

Status: Active

Transition Washer for Connecting Aluminum/Aluminum, Aluminum/Copper and Aluminum/Copper Lugs and Bus Bar, Outer Diameter 25.4mm (1.0 Inch), Inner Diameter 8.6mm (0.34 Inch), Stud Size 5/16 Inch, Copper Alloy, Tin Plated

- Teeth on the transition washers penetrate aluminum and copper oxides, enabling copper to aluminum connections to be made in a bolted joint without the use of inhibiting compounds.
- Transition washers also accommodate the difference in thermal expansion between copper and aluminum, and enhances the efficiency of bolted grounding connections.

North American Specifications (UNSPSC)		
UNSPSC	31161807 Flat washers	
IGCC	2885 Flat washers	
Brand Name	Color-Keyed	
Туре	Transition Washer	
Application	Teeth on the transition washers penetrate alu-	
	minum and copper oxides, enabling copper to alu-	
	minum connections to be made in a bolted joint	
	without the use of inhibiting compounds.	
Standard	UL E9809	
Material	Copper Alloy	
Finish	Tin Plated	
Thickness	0.035 Inch/0.89mm	
Outside Diameter	1 Inch/25.4mm	
Inside Diameter	0.34 Inch/8.6mm	
Fits Bolt Sizes	5/16 Inch	
Color	Silver	

European Specifications (ETIM)		
ETIM	EC002345 Serrated lock washer	
Material	Other	
Material quality	Other	
Surface protection	Other	
Model	Double toothing	
Inner diameter	8.6mm	
Outer diameter	25.4mm	
Thickness	0.89mm	

Packaging		
Inner Quantity	100	
Inner Dimensions (inches)	3.3x2.8x2.3	
Outer Quantity	1000	
Outer Dimensions (inches)	12.2x6x3.4	
Weight Llom	9.38 lbs_per 1000	

Documents / Support Tools	
Technical Drawing / Data Sheet	WSD-000471
Technical Drawing / Data Sheet Canada	Available on Website

For further technical assistance, please contact us...

ABB Installation Products Technical Support MS 3B-50



Memphis, TN 38120 www.tnb.com

860 Ridge Lake Blvd. Memphis, TN 38120 Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com