



Himeline® Enclosures

HP Series Enclosures with Hinged Quick-Release Cover



Depth with back panel installed



ENCLOSURE WITH OPAQUE COVER CAT. NO.	STD. WT. (LBS.)	ENCLOSURE WITH CLEAR WINDOW*	STD. WT. (LBS.)	WINDOW DIMENSIONS (H X W) (IN.)	DIMENSIONS (IN.)										STD. CTN.
					EXTERNAL			INTERNAL			MOUNTING		WINDOW		
					A	B	C	D	E	F	G	H	J	K	
HP1612B	11.04	HC1612B	12.5	11 x 7.87	16.93	12.99	7.87	14.96	10.24	6.61	14.76	5.91	11.02	7.87	1
HP2016B	16.80	HC2016B	17.2	14.96 x 11.81	20.87	16.93	7.87	18.90	14.17	6.61	18.70	9.84	14.96	11.81	1
HP2416C	21.13	HC2416C	24.12	18.89 x 11.81	25.47	17.17	9.84	22.83	14.17	8.35	22.64	9.84	18.90	11.81	1
HP3020D	32.28	HC3020**	36.02	22.83 x 15.74	29.41	21.10	11.81	26.77	18.11	10.28	26.57	13.78	22.83	15.75	1
HP3325D	39.00	HC3325D**	43.12	26.77 x 19.68	33.35	25.04	11.81	30.71	22.05	10.28	30.51	17.72	26.77	19.69	1



* HC Enclosures are IP 65 Rated. Clear window is glass.

** This series of enclosures comes standard with body, lid and mounting rail kit.

Consult Customer Service for availability and delivery.

Hinged Internal Door

- Internal fiberglass-reinforced polyester door assembly
- Grid pattern on the inside for quicker positioning of equipment
- Quick-locking 1/4-turn entry



CAT. NO.	A		B		C		D		STD. CTN.	STD. WT. (LBS.)
	IN.	(MM)	IN.	(MM)	IN.	(MM)	IN.	(MM)		
PID1612	12.40	(315)	18.07	(205)	5.98	(152)	1.02	(26)	1	2.05
PID2016B	16.34	(415)	12.00	(305)	5.98	(152)	1.02	(26)	1	3.15
PID2416C	20.28	(515)	12.00	(305)	7.64	(194)	1.26	(32)	1	4.50
PID3020D	24.21	(615)	15.94	(405)	9.61	(244)	1.26	(32)	1	6.50
PID3325D	28.15	(715)	19.88	(505)	9.61	(244)	1.26	(32)	1	8.45