

General-Purpose Cable Ties and Accessories

Catamount® Ties fit the needs of general-purpose fastening. Installers quickly discover that Catamount® products offer durable and value-priced cable bundling for a variety of commercial and residential construction applications. Catamount® Ties are offered in a wide range of sizes, styles and colors and meet the requirements for most fastening projects. Catamount® Cable Ties are UL Recognized per File #E-4905.

Miniature — Series 18

CAT. NO.	LENGTH (IN.)	WIDTH (IN.)	MAX. BUNDLE DIA. (IN.)	COLOR	STD. QTY.
L-4-18-9-C	4.0	.100	¾	Natural	100
L-4-18-9-M	4.0	.100	¾	Natural	1,000
L-4-18-0-C	4.0	.100	¾	UV Black	100
L-4-18-0-M	4.0	.100	¾	UV Black	1,000
L-6-18-9-M	6.4	.100	1½	Natural	1,000
L-8-18-9-C	8.0	.100	2	Natural	100
L-8-18-9-M	8.0	.100	2	Natural	1,000
L-8-18-0-C	8.0	.100	2	UV Black	100
L-8-18-0-M	8.0	.100	2	UV Black	1,000

Intermediate — Series 30/40

CAT. NO.	LENGTH (IN.)	WIDTH (IN.)	MAX. BUNDLE DIA. (IN.)	COLOR	STD. QTY.
L-5-30-9-C	5.6	.130	1¼	Natural	100
L-5-30-9-M	5.6	.130	1¼	Natural	1,000
L-5-30-0-C	5.6	.130	1¼	UV Black	100
L-5-30-0-M	5.6	.130	1¼	UV Black	1,000
L-8-40-9-C	8.5	.140	2	Natural	100
L-8-40-9-M	8.5	.140	2	Natural	1,000
L-8-40-0-C	8.5	.140	2	UV Black	100
L-8-40-0-M	8.5	.140	2	UV Black	1,000
L-11-40-9-C	11.5	.146	3	Natural	100
L-11-40-9-M	11.5	.146	3	Natural	1,000
L-11-40-0-C	11.5	.146	3	UV Black	100
L-11-40-0-M	11.5	.146	3	UV Black	1,000
L-14-40-9-C	14.5	.146	4	Natural	100
L-14-40-9-M	14.5	.146	4	Natural	1,000
L-14-40-0-C	14.5	.146	4	UV Black	100
L-14-40-0-M	14.5	.146	4	UV Black	1,000

Standard — Series 50

CAT. NO.	LENGTH (IN.)	WIDTH (IN.)	MAX. BUNDLE DIA. (IN.)	COLOR	STD. QTY.
L-7-50-9-C	7.5	.187	1¾	Natural	100
L-7-50-9-M	7.5	.187	1¾	Natural	1,000
L-7-50-0-C	7.5	.187	1¾	UV Black	100
L-7-50-0-M	7.5	.187	1¾	UV Black	1,000
L-11-50-9-C	11.1	.187	3	Natural	100
L-11-50-9-D	11.1	.187	3	Natural	500
L-11-50-0-C	11.1	.187	3	UV Black	100
L-11-50-0-D	11.1	.187	3	UV Black	500
L-14-50-9-C	14.1	.187	4	Natural	100
L-14-50-9-D	14.1	.187	4	Natural	500
L-14-50-0-C	14.1	.187	4	UV Black	100
L-14-50-0-D	14.1	.187	4	UV Black	500

Heavy-Duty

CAT. NO.	LENGTH (IN.)	WIDTH (IN.)	MAX. BUNDLE DIA. (IN.)	COLOR	STD. QTY.
Series 120					
L-8-120-0-C	8.0	.300	2	UV Black	100
L-11-120-9-C	11.1	.300	3	Natural	100
L-11-120-0-C	11.1	.300	3	UV Black	100
L-14-120-9-C	14.2	.300	4	Natural	100
L-14-120-0-C	14.2	.300	4	UV Black	100
L-18-120-9-L	18.0	.300	4¾	Natural	50
L-18-120-0-L	18.0	.300	4¾	UV Black	50
L-24-120-9-Q	24.2	.300	7	Natural	25
L-24-120-9-L	24.2	.300	7	Natural	50
L-24-120-0-Q	24.2	.300	7	UV Black	25
L-24-120-0-L	24.2	.300	7	UV Black	50
L-24-120-2-L	24.2	.300	7	Red	50
L-28-120-9-L	28.0	.300	8	Natural	50
L-28-120-0-L	28.0	.300	8	UV Black	50
Series 175					
L-24-175-9-L	24.0	.345	7.2	Natural	50
L-24-175-0-L	24.0	.345	7.2	UV Black	50
L-36-175-9-L	36.0	.345	10¾	Natural	50
L-36-175-0-L	36.0	.345	10¾	UV Black	50
L-48-175-9-L	48.0	.345	15	Natural	50
L-48-175-8-L	48.0	.345	15	Gray	50
L-48-175-0-L	48.0	.345	15	UV Black	50
Series 250					
L-28-250-0-L	28.0	.345	8	UV Black	50

For installation tools, see pp. C-46-C-48.

Sample Catalog Order

Length Style Color

L 4 18 R 9 C

Tensile Strength Quantity

4" Length, 18-lb. Tensile Strength, Releasable Tie, Natural Color, 100-Pack Quantity

Color

0 – Black (UV Resistant) 9 – Natural
8 – Gray

Pack Quantity

L = 50 D = 500
C = 100 M = 1,000

Style

R = Releasable MH = Mounting Head