

TECHNICAL DATA SHEET

PMA Divisible System - PACOF - Corrugated Conduit

Flexible, medium-duty, IP40

PMA



Divisible conduit ideal for retrofit and repairs with global rail fire safety specification



Applications:

- Rail, machine building and many other applications

Features & Benefits:

- Easy installation and reopening if necessary
- PMA standard nominal widths can be used in combination with all PMA fittings and accessories
- Trouble-Free retrofitting
- Applicable also for repairs
- Self-extinguishing

Materials:

- Specially modified polyamide 6

Compatible with:

- BLNO-M divisible fittings
- BLN-M divisible locknuts
- All standard PMA fittings and accessories

Temperature range:

- -40°C ... +105°C continuous, +160°C short-term

Conforms to:

- EN 45545-2 HL3 (R22 & R23)
- NFPA 130

Weathering resistance:

- Very good UV resistance and weathering characteristics

Colour:

- Black

Chemical properties:

- Please refer to www.pma.ch
(Technical Information / Chemical Resistance)

Environmental properties:

- Free from halogens and cadmium
- RoHS and REACH compliant


PACOF-Index

min.					max.
Ductility					
Fatigue reversed bending					
Compression resistance					
Low temperature performance					
Weathering resistance					

Product selection:

Part no.	Conduit size		fits to		rec. fitting thread size	Dimensions in mm (nom.)						Weight	Packing unit
black	NW	metric	system support	PMA fittings for NW	metric	d1	d2	stat. R	a	b	s min.	kg/100 m	metre
PACOF-07B	7	10	BFH-07-0	7	M12x1.5	5.6	10.0	30	3.2	2	0.15	2.0	50
PACOF-10B	10	12	BFH-10-0	10	M12x1.5	8.5	12.8	33	3.6	2.2	0.15	3.6	50
PACOF-12B	12	16	BFH-12-0	12	M16x1.5	11.0	15.6	35	3.5	2.1	0.15	5.3	50
PACOF-17B	17	20	BFH-17-0	17	M20x1.5	15.5	21.1	45	4.1	2.6	0.15	6.8	50
PACOF-23B	23	25	BFH-23-0	23	M25x1.5	22.1	28.4	70	4	2.3	0.2	11.0	50
PACOF-29B	29	32	BFH-29-0	29	M32x1.5	27.2	34.5	120	4.1	2.5	0.2	15.5	50
PACOF-36B	36	40	BFH-36-0	36	M40x1.5	32.0	42.4	145	8.2	5	0.3	19.5	30
PACOF-48B	48	50	BFH-48-0	48	M50x1.5	43.9	54.5	150	7	4.7	0.3	26.2	30
PACOF-70B	70	80	-	PMAGRIP flange NW70	-	62.0	79.0	190	8.6	5.1	0.25	53.0	10

Our customer service dept. or local distribution partner will be pleased to help you concerning product availability and lead time



stat. R. = min. bending radius for static (fixed) installation

Mechanical Properties:	Value:	Test parameters:	Test method:
Impact strength	> 4.5 J		PMA DO 9.21-4330
Compression strength	> 180 N		PMA DO 9.21-4320
Pull-out resistance conduit - fitting series			
PMA Divisible System - BLNO	> 125 N		PMA DO 9.21-4610

Note: Testing at 23°C, 50% r.h., conduit nominal width 17, unless otherwise stated

Thermal properties:	Value:	Test parameters:	Test method:
Continuous application temperature	- 40 ... +105°C		PMA DO 9.21-4510
Upper application temperature	+120°C	(20'000 h)	
Short-term	+160°C	(168 h)	

Fire safety properties:	Value:	Test parameters:	Test method:
Fire Performance	V0		UL 94
Fire hazard level	HL3		EN 45545-2 (R22)
Oxygen index	> 32 %		EN ISO 4589-2
Smoke density	< 150 Ds max.		EN ISO 5659-2 (25 kW/m2)
Toxicity	< 0.75 CIT _{NLP}		NF X 70-100-1/-2: (600°C)
Fire hazard level	HL3		EN 45545-2 (R23)
Oxygen index	> 32 %		EN ISO 4589-2
Smoke density	< 300 Ds max.		EN ISO 5659-2 (25 kW/m2)
Toxicity	< 1.5 CIT _{NLP}		NF X 70-100-1/-2: (600°C)
Fire performance NFPA 130:			NFPA 130
- Flammability	compliant		ASTM E 162
- Smoke density	compliant		ASTM E 662
Heat and visible smoke	22.7 MJ/kg		ASTM E 1354
Smoke emission toxicity	compliant		Bombardier SMP 800-C
Smoke emission toxicity	compliant		Boeing BSS 7239

Note: Requirement sets (R22 & R23) apply for conduit sizes up to and including NW48

ABB Switzerland Ltd,
PMA Cable Protection
Aathalstrasse 90
8610 Uster, Switzerland
Phone: +41 58 585 00 11
pma-info@ch.abb.com
www.pma.ch

Let's write the future.
Together. **abb.com**

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Installation Products Inc. does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB Inc. Copyright© 2019 ABB Installation Products Inc. All rights reserved

