



Family

Catalog Number: PCLT-12B.50
Product ID: 7TAA292240R0080
UPC Number: 78620996705
EAN Number: 07630030269035
Status: Active

Fine Profile Medium Wall Very Flexible Black Conduit, (PCL) Material - Polyamide 6, Conduit Size NW - 12, 50 Meters

- Very good flexibility
- Good mechanical strength at low temperatures and dry conditions
- Self-extinguishing
- Free from halogens and cadmium
- Machine building, installation and vehicle building applications

North American Specifications (UNSPSC)

| | |
|------------------|-----------------------------|
| UNSPSC | 39131706 Electrical conduit |
| IGCC | 5535 Electrical conduit |
| Brand Name | PMA |
| Type | Medium Wall Conduit |
| Application | Machine |
| Standard | CSA |
| Trade Size | NW12 |
| Outside Diameter | 0.62 Inch |
| Inside Diameter | 0.47 Inch |
| Length | 50 Meters |
| Flexibility | Very Flexible |
| Material | Polyamide/Nylon 6 |
| Color | Black |

European Specifications (ETIM)

| | |
|--|----------------------------------|
| ETIM | EC001175 Corrugated plastic hose |
| Nominal diameter | 16mm |
| Outer diameter | 15.8mm |
| Inner diameter | 12mm |
| Material | Polyamide 6 |
| Compressive strength | 150N |
| Operating temperature | -50 - +105°C |
| Fire resistance in accordance with UL94 | V2 |
| UV resistant | Y |
| Colour | Black |
| Sheathing material | Not sheathed |
| Bending strength | Flexible |
| Lengthwise slotted | N |
| Closable (two-part) | N |
| Halogen free | Y |
| Approved according to DIN EN 61386-23 | N |
| Approved according to UR | Y |
| Approved according to CSA | Y |
| Approved according to LUL/British Standard | Y |
| Approved according to Lloyd's Register TA | Y |
| Approved according to UTAC | N |
| Approved according to DIN 5510 | N |
| Approved according to NF F 16-101 | N |

Packaging

| | |
|---------------------------|----------------------|
| Inner Quantity | 1 |
| Outer Quantity | 20 |
| Outer Dimensions (inches) | 47.244x31.496x29.528 |
| Weight Uom | 4.4 lbs. Each |

Documents / Support Tools

| | |
|-------------------------|----------------------|
| Technical Data Sheet CA | Available on Website |
|-------------------------|----------------------|

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com