

# Snap-N-Stac™ Combo Spacers

## Specifications

Description	Part Number	Size	Separation	Std. Ctn. Qty.	Std. Ctn. Wt. (lbs.)
1-Way Spacers	SP2W20-1	2"	2"	56	15.0
	SP2W30-1	2"	3"	40	13.0
	SP4W15-1	4"	1-1/2"	26	9.6
	SP4W20-1	4"	2"	20	10.0
	SP4W30-1	4"	3"	20	9.4
2-Way Spacers	SP2W20-2*	2"	2"	56	28.5
	SP2W30-2*	2"	3"	40	23.8
	SP3W20-2	3"	2"	40	24.0
	SP3W30-2	3"	3"	24	17.9
	SP4W15-2*	4"	1-1/2"	26	18.3
	SP4W20-2*	4"	2"	24	18.8
	SP4W30-2*	4"	3"	20	17.6
	SP5W20-2	5"	2"	20	17.2
	SP5W30-2	5"	3"	14	15.5
	SP6W20-2	6"	2"	12	12.8
3-Way Spacers	SP6W30-2	6"	3"	12	14.1
	SP2W20-3	2"	2"	36	28.5
	SP2W30-3	2"	3"	18	17.8
	SP4W15-3	4"	1-1/2"	18	19.4
	SP4W20-3	4"	2"	16	19.3
	SP4W30-3	4"	3"	14	19.1

\*Can be cut apart to make (2) one-way spacers

### How to Interpret the Part Number


Position 1	Position 2	Position 3	Position 4
Product Type	Duct Size	Duct-To-Duct Spacing - Horizontal and Vertical	Horizontal Duct Positions
SP = Spacer	2W = 2" Width	15 = 1-1/2"	-1 = One-Way
	3W = 3" Width	20 = 2"	-2 = Two-Way
	4W = 4" Width	30 = 3"	-3 = Three-Way
	5W = 5" Width		
	6W = 6" Width		

## Accessories



Snap-Loc® Reducer

Part No.	Size	Std. Ctn. Qty.
S287F	1"	100
S287J	2"	100



Beaded Strap

Part No.	Std. Ctn. Qty.
S28612	100

## Technical Information

Part Number	Duct Size	Duct OD	Horizontal Duct Positions	Duct-To-Duct Spacing		Center-To-Center Spacing		Bottom of Trench to Bottom of Duct	Bottom of Trench to Center of Bottom Duct	Overall Length
				Vertical (Inches)	Horizontal (Inches)	Vertical	Horizontal			
SP2W20-1	2"	2.375	1	2	2	2.19	2.19	3.13	4.25	4.38
SP2W30-1	2"	2.375	1	3	3	2.69	2.69	4.13	5.25	5.38
SP4W15-1	4"	4.500	1	1.5	1.5	3.00	3.00	3.38	5.56	6.00
SP4W20-1	4"	4.500	1	2	2	3.25	3.25	3.88	6.06	6.50
SP4W30-1	4"	4.500	1	3	3	3.75	3.75	4.88	7.06	7.50
SP2W20-2	2"	2.375	2	2	2	4.38	4.38	3.13	4.25	8.75
SP2W30-2	2"	2.375	2	3	3	5.38	5.38	4.13	5.25	10.75
SP3W20-2	3"	3.500	2	2	2	5.50	5.50	3.63	5.38	11.00
SP3W30-2	3"	3.500	2	3	3	6.50	6.50	4.63	6.38	13.00
SP4W15-2	4"	4.500	2	1.5	1.5	6.00	6.00	3.38	5.56	12.00
SP4W20-2	4"	4.500	2	2	2	6.50	6.50	3.88	6.06	13.00
SP4W30-2	4"	4.500	2	3	3	7.50	7.50	4.88	7.06	15.00
SP5W20-2	5"	5.500	2	2	2	7.56	7.56	4.38	7.25	15.12
SP5W30-2	5"	5.500	2	3	3	8.56	8.56	5.38	8.25	17.14
SP6W20-2	6"	6.625	2	2	2	8.62	8.62	4.13	7.38	17.25
SP6W30-2	6"	6.625	2	3	3	9.62	9.62	5.13	8.38	19.25
SP2W20-3	2"	2.375	3	2	2	6.57	6.57	3.13	4.25	13.13
SP2W30-3	2"	2.375	3	3	3	8.07	8.07	4.13	5.25	16.13
SP4W15-3	4"	4.500	3	1.5	1.5	9.00	9.00	3.38	5.56	18.00
SP4W20-3	4"	4.500	3	2	2	9.75	9.75	3.88	6.06	19.50
SP4W30-3	4"	4.500	3	3	3	11.25	11.25	4.88	7.06	22.50