



Actual

**Catalog Number:** TYPEA75-175  
**Product ID:** 7TAD012530R0002  
**UPC Number:** 78621097672  
**EAN Number:** 05414363183068  
**Status:** Active

3/4 Inch Non-metallic Orange Type A Liquidtight Conduit

- Smooth, seamless inner core of flexible PVC that is bonded to a coursing of flexible PVC. Between these layers is a woven nylon mesh molded for reinforcement.
- Sunlight resistant
- Meets NEC, article 351, part "B" (ANSI/NFPA-70) for flexible liquidtight non-metallic conduit.

### North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	T&B
Type	Type A-Non-Metallic Liquidtight Conduit
Special Features	No Metal Core to Fatigue from Flexing or Vibration
Application	Ideally Suited for Continuous Flexing Applications or Vibration
Standard	UL E95745
Trade Size	3/4 Inch
Material	PVC
Color	Orange

### European Specifications (ETIM)

ETIM	EC001177 Protective plastic hose
Nominal size in inch	3/4 inch
Material	PVC
Sheathing material	Other
Operating temperature	-20-+60°C
UV resistant	Y
Flexibility	Flexible
Colour	Orange
Approved according to CSA	Y

### Packaging

Outer Quantity	175
Outer Dimensions (inches)	35x35x7
Weight Uom	35.38 lbs. per 100

### Documents / Support Tools

Technical Drawing / Data Sheet	WSD-000172
--------------------------------	------------

**For further technical assistance, please contact us...**

ABB Installation Products - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

ABB Installation Products Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)