

COMPACT PENDANT ARM SERIES 1, TYPE 12



INDUSTRY STANDARDS

NEMA/EEMAC Type 12
IEC 60529, IP65
DIN 40050

APPLICATION

The Series 1 Compact Pendant Arm provides a flexible and easy-to-use method for mounting and positioning small or lightweight HMI controls and instruments, up to 30 lbs. The Compact Pendant Arm is easily attached to a machine or wall and moves both horizontally and vertically to suit the user's needs and preferences.

SPECIFICATIONS

- Cast aluminum and extruded aluminum tube
- Four pre-assembled models. One model capable of horizontal and vertical motion. One model capable of horizontal motion. Either model is available in two lengths, 500 mm or 800 mm.
- Internal braking mechanism (vertical motion only) prevents downward "free-fall" motion when locked
- Easily removable snap-on cover provides access to wire containment channel
- Adjustable enclosure mounting. Arm can be configured to mount to top, bottom or back of an enclosure.
- Enclosure mounting plate can be rotated, tilted and locked into desired position
- Handle available as option


FINISH

Tube is anodized. Color is silver. Fittings and snap-on cover are RAL 7035 light-gray polyester powder paint.

BULLETIN: CS4

Standard Product

Catalog Number	Description	L	Maximum Load
CCS1H5V	Vertical and horizontal motion	500 mm	30 lbs.
CCS1H8V	Vertical and horizontal motion	800 mm	15 lbs.
CCS1H8	Horizontal motion	800 mm	15 lbs.



HANDLE

Mounts to end of arm in pre-threaded hole.

BULLETIN: CS4

Catalog Number	Color
CCS1HDL	Black