Cable/Conduit Clip








- Supports conduit to rod, wire or flange
- Can also be used for flexible metallic tubing, armored cable, portable cables, control tubes and communications cable
- Available for EMT, rigid, ENT, IMT, MC/AC and aluminum conduit
- No installation tools required







Material: Spring Steel Finish: CADDY ARMOUR



| Part Number | Article Number | Outer Diameter OD | Static Load 1 F1 | Static Load 2 F2 | Static Load 3 F3 | Standard Packaging Quantity |
|-------------|----------------|----------------------|---------------------|---------------------|---------------------|--------------------------------|
| K8 | 170660 | 18 mm Max | 220 N | 445 N | 110 N | 100 pc |
| K12 | 170670 | 24 mm Max | 220 N | 445 N | 110 N | 100 рс |
| K16 | 170680 | 30 mm Max | 220 N | 445 N | 110 N | 100 pc |
| K20 | 170690 | 42 mm Max | 220 N | 445 N | 110 N | 100 pc |

| Part Number | Outer Diameter | Rod Size |
|-------------|----------------|----------|
| K8 | 8 mm - 18 mm | M4; M6 |
| K12 | 14 mm - 20 mm | M12 |
| K12 | 16 mm - 22 mm | M8; M10 |
| K12 | 18 mm - 24 mm | M4; M6 |
| K16 | 22 mm - 24 mm | M12 |
| K16 | 24 mm - 26 mm | M8; M10 |
| K16 | 26 mm - 30 mm | M4; M6 |
| K20 | 20 mm - 36 mm | M12 |
| K20 | 25 mm - 38 mm | M8; M10 |
| K20 | 30 mm - 42 mm | M4; M6 |
| KX | 4 mm - 12 mm | M4; M6 |





| Part Number | Outer Diameter | Flange Thickness |
|-------------|----------------|------------------|
| K8 | 3 mm - 7 mm | 12 mm - 16 mm |
| K12 | 3 mm - 7 mm | 16 mm - 22 mm |
| K12 | 8 mm - 10 mm | 14 mm - 20 mm |
| K12 | 11 mm - 13 mm | 12 mm - 19 mm |
| K16 | 3 mm - 7 mm | 24 mm - 28 mm |
| K16 | 8 mm - 10 mm | 20 mm - 26 mm |
| K16 | 11 mm - 13 mm | 19 mm - 24 mm |
| K20 | 3 mm - 7 mm | 28 mm - 40 mm |
| K20 | 8 mm - 10 mm | 26 mm - 38 mm |
| K20 | 11 mm - 13 mm | 21 mm - 35 mm |
| KX | 6 mm - 12 mm | 3 mm - 5 mm |

May require dedicated drop wire/rod and EC311. Consult local authority. For horizontal application only when installing conduit.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved
Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.
All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.



