nVent CADDY Speed Link SLK with Y-Hook - SLK2YH500L3R2













- Complete system includes wire, locking device and two pre-assembled hook end fittings
- Fastens to the building structure and hooks to hanging services and tray
- Spring latch helps provide secure connection
- Convenient design allows one hook to be temporarily detached for maintenance or to add cables to the tray
- Single drop with double hook provides increased stability to the system
- Also available in a single-hook end fitting configuration









Part Number	SLK2YH500L3R2
Material	Steel Zinc Alloy Polypropylene
Finish	Electrogalvanized
Static Load Safety Factor	5:1
Complies With	SMACNA HVAC-DCS
Wire Rope Diameter	2 mm
Wire Rope Length	9.9'
Wire Rope "Y" Length (YL)	19.6"
А	2.3"
В	0.9"
С	1/4"
Static Load (F)	100 lb
Height (H)	2.15"
Width (W)	3/4"
Thickness (T)	1/2"
Angle (a)	90° Max
Certifications	cULus



Part Number	SLK2YH500L3R2
Standard Packaging Quantity	15 x 2 pc
UPC	78285685126
EAN-13	8711893144741

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nevent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

