


Wide Span Cable Tray

perforated, with continuous perforated and beaded side profiles

WRL 105.300

EAN Code: 4013339310807

the photorealistic images are to be considered as reference images



Article Description

Wide span cable tray, 105x300x6000 mm, t=1,5 mm, perforated, steel, pre-galvanised according to DIN EN 10346

Additional Price Information

Article group	N13
---------------	-----

Weight

Weight per quantity unit	6,842 kg
Weight in kg per 100	684 kg

Physical Article Dimensions

Height	105.00 mm
Width	300 mm
Depth/length	6000 mm


Technical Datasheet

Long Span Cable Tray

WRL 105.300

the photorealistic images are to be considered as reference images

Load Specifications



Packing Dimension

6 meters = 1 piece		✓ VP1-smallest packaging unit (PU)		✓ VP1-preferred PU	
Lenght	6000 mm	Width	300 mm	Height	105.00 mm
Gross weight	41 kg	Volume	0,189 m³		
Min. quantity	6	Max. Quantity	6		

84 meters = 1 bundle					
Lenght	6000 mm	Width	330 mm	Height	860 mm
Gross weight	574 kg	Volume	1,703 m³		
Min. Quantity	84.00	Max. Quantity	84.00		

Tender Text

Wide span cable tray, acc. to DIN EN 61537, with continuous perforated and beaded side beams, as well as riveted bottom with offset perforation and perforated cross beads for stabilisation and barrier strip fastening. Please order splice plate WSV 105.390 separately.

Dimensions (approx. dimensions)

Height H x Width W : 105 x 300 mm

Material thickness : 1.5 mm

Cross section distance : 300 mm

Side beam perforation : 9.5 x 13 mm

Hole distance : 50 mm

Delivery length : 6000 mm

Usable cross-section : 24715 mm²

Material : steel, pre-galvanised acc. to DIN EN 10346

NIEDAX Model No. : WRL 105.300

EP Material_____ EP wage_____

Unit price/meter

Technical Datasheet

Long Span Cable Tray

WRL 105.300

the photorealistic images are to be considered as reference images

Safety & Environment

REACH Date	23.01.2024
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73089059

Related items

Cover

Model No.	Description
WDRS 20	Turning bolt with locknut acc. to DIN EN ISO 10511, for WSL/WRL, steel, pre-galvanised according to DIN EN 10346, incl. accessories
WDV 300	Cover for WSL/WRL, w. joint strip, 304x3000 mm, with turning lock, steel, pre-galvanised according to DIN EN 10346

Barrier strip

Model No.	Description
KLWC 16	Barrier strip fastening clamp, for 16 mm slot width, steel, pre-galvanised according to DIN EN 10346, incl. accessories
RW 85	Barrier strip, 80x3000 mm, t=0,9 mm, steel, pre-galvanised according to DIN EN 10346, incl. accessories

Connector

Model No.	Description
WSV 105.390	Splice plate, 106,5x390 mm, steel, pre-galvanised according to DIN EN 10346, incl. accessories

Accessories

Model No.	Description
WHAS 105 S	Wide span beam connection piece, height 105 mm, steel, pre-galvanised acc. to DIN EN 10346, incl. accessories