


Wide Span Cable Tray

perforated, with continuous perforated and beaded side profiles

WRL 150.300 F

EAN Code: 4013339590605

the photorealistic images are to be considered as reference images



Article Description

Wide span cable tray, 150x300x6000 mm, t=1,5 mm, perforated, steel, hot dip galvanised DIN EN ISO 1461

Additional Price Information

Article group	N13
---------------	-----

Weight

Weight per quantity unit	8,704 kg
Weight in kg per 100	870 kg

Physical Article Dimensions

Height	150.00 mm
Width	300 mm
Depth/length	6000 mm

Technical Datasheet


Long Span Cable Tray

WRL 150.300 F

the photorealistic images are to be considered as reference images

Load Specifications

Load diagram: q = evenly distributed cable load (tested acc. to DIN EN IEC 61537)



Fixing distance (m)

The load details shown in the diagram are independent of the position of the connectors.

Packing Dimension

6 meters = 1 piece

Min. quantity	6	Max. Quantity	6
---------------	---	---------------	---

Tender Text

Wide span cable tray, acc. to DIN EN 61537, with continuous perforated and beaded side beams, as well as riveted bottom with offset perforation and perforated cross beads for stabilisation and barrier strip fastening. Please order splice plate WSV 150.500 separately.

Dimensions (approx. dimensions)

Height H x Width : 150 x 300 mm

Material thickness : 1.5 mm

Cross section distance : 300 mm

Side beam perforation : 9.5 x 13 mm

Hole distance : 50 mm

Delivery length : 6000 mm

Usable cross-section : 38215 mm²

Material : steel, hot-dup galvanised acc. to DIN EN ISO 1461

NIEDAX Model No. : WRL 150.300 F

EP material _____ EP wage _____

Unit price/meter

Safety & Environment

REACH Date	23.01.2024
------------	------------

REACH Info	Conformable
------------	-------------

RoHS Info	Conformable
-----------	-------------

Technical Datasheet

Long Span Cable Tray

WRL 150.300 F

the photorealistic images are to be considered as reference images

Origin & International Trade

Country of origin	DE
Customs tariff number	73089059

Related items

Cover

Model No.	Description
WDRS 20 F	Turning bolt with locknut acc. to DIN EN ISO 10511, for WSL/WRL, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories
WDV 300 F	Cover for WSL/WRL, w. joint strip, 304x3000 mm, with turning lock, steel, hot dip galvanised DIN EN ISO 1461

Barrier strip

Model No.	Description
KLWC 16 F	Barrier strip fastening clamp, for 16 mm slot width, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories
RW 110 F	Barrier strip, 98x3000 mm, t=0,9 mm, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories

Connector

Model No.	Description
WSV 150.500 F	Splice plate, 151,5x500 mm, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories