


Wide Span Cable Tray

perforated, with continuous perforated and beaded side profiles

WRL 200.400 F

EAN Code: 4013339593408

the photorealistic images are to be considered as reference images



Article Description

Wide span cable tray, 200x400x6000 mm, t=1,5 mm, perforated, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories

Technical Datasheet

Long Span Cable Tray

WRL 200.400 F

the photorealistic images are to be considered as reference images

Incl. accessories

6 meter = 1 piece		✓ lowest delivery unit	✓ preferred delivery unit
Model No.	Description	quantity	
FLM 6X12 F	Mushroom-head bolt M6, similar DIN 603, length 12 mm, steel, hot dip galvanised DIN EN ISO 1461	4 pcs.	
RSL 400 F	Joint bar for wide span cable tray, B=389 mm, for bottom stabilisation, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories	1	
48 meter = 1 bundle		- lowest delivery unit	- preferred delivery unit
Model No.	Description	quantity	
FLM 6X12 F	Mushroom-head bolt M6, similar DIN 603, length 12 mm, steel, hot dip galvanised DIN EN ISO 1461	32 pcs.	
RSL 400 F	Joint bar for wide span cable tray, B=389 mm, for bottom stabilisation, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories	8	

Additional Price Information

Article group	N13
---------------	-----


Weight

Weight per quantity unit	11 kg
Weight in kg per 100	1093 kg

Physical Article Dimensions

Height	200.00 mm
Width	400 mm
Depth/length	6000 mm

Load Specifications



Technical Datasheet

Long Span Cable Tray

WRL 200.400 F

the photorealistic images are to be considered as reference images

Packing Dimension

6 meters = 1 piece		✔ VP1-smallest packaging unit (PU) ✔ VP1-preferred PU			
Lenght	6000 mm	Width	400 mm	Height	200.00 mm
Gross weight	66 kg	Volume	0,480 m³		
Min. quantity	6	Max. Quantity	6		

48 meters = 1 bundle					
Lenght	6000 mm	Width	430 mm	Height	860 mm
Volume	2,219 m³				
Min. Quantity	48.00	Max. Quantity	48.00		

Tender Text

Wide span cable tray, acc. to DIN EN 61537, with continuous perforated and corrugated side beams, as well as riveted bottom with offset perforation and perforated cross beads for stabilisation and barrier strip fastening, including a joint bar RSL... and proportional fastening accessories in hot-dip galvanised. Please order splice plate WSV 200.500 separately. Dimensions (approx. dimensions) H x W : 200 x 400 mm Material thickness : 1.5 mm Cross-section thickness distance : 300 mm Side beam perforation : 9.5 x 13 mm Hole distance : 50 mm Delivery length : 6000 mm Usable cross-section : 71475 mm² Material : Steel, hot-dip galvanised acc. to DIN EN ISO 1461 NIEDAX Model No. : WRL 200.400 F EP Material_____ EP Wage_____ Unit price/meter	
--	--

Safety & Environment

REACH Date	23.01.2024
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73089059

Related items

Cover

Model No.	Description
WDRS 20 F	Turning bolt with locknut acc. to DIN EN ISO 10511, for WSL/WRL, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories
WDV 400 F	Cover for WSL/WRL, w. joint strip, 404x3000 mm, with turning lock, steel, hot dip galvanised DIN EN ISO 1461

Technical Datasheet

Long Span Cable Tray

WRL 200.400 F

the photorealistic images are to be considered as reference images

Related items

Barrier strip

Model No.	Description
KLWC 16 F	Barrier strip fastening clamp, for 16 mm slot width, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories
RW 110 F	Barrier strip, 98x3000 mm, t=0,9 mm, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories

Connector

Model No.	Description
WSV 200.500 F	Splice plate, 201,5x500 mm, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories