


Wide Span Cable Tray

unperforated, with unperforated and beaded side profiles, but with connector perforations

WRU 200.600 F

EAN Code: 4013339594108

the photorealistic images are to be considered as reference images



Article Description

Wide span cable tray, 200x600x6000 mm, t=1,5 mm, unperforated, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories

Incl. accessories

6 meter = 1 piece

✓ lowest delivery unit

✓ preferred delivery unit

Model No.	Description	quantity
FLM 6X12 F	Mushroom-head bolt M6, similar DIN 603, length 12 mm, steel, hot dip galvanised DIN EN ISO 1461	4 pcs.
RSL 600 F	Joint bar for wide span cable tray, B=589 mm, for bottom stabilisation, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories	1

Additional Price Information

Article group N13

Technical Datasheet

Long Span Cable Tray

WRU 200.600 F

the photorealistic images are to be considered as reference images


Weight

Weight per quantity unit	13 kg
Weight in kg per 100	1320 kg

Physical Article Dimensions

Height	200.00 mm
Width	600 mm
Depth/length	6000 mm

Load Specifications



Packing Dimension

6 meters = 1 piece		✓ VP1-smallest packaging unit (PU)		✓ VP1-preferred PU	
Lenght	6000 mm	Width	600 mm	Height	200.00 mm
Gross weight	79 kg	Volume	0,720 m³		
Min. quantity	6	Max. Quantity	6		

Tender Text

Wide span cable tray, acc. to DIN EN 61537, with unperforated and beaded side beams, with connector perforation for connection, as well as riveted bottom with unperforated cross beads for stabilisation, including a joint bar RSL... and proportional fastening accessories in hot-dip galvanised. Please order WSV 200.500 splice plate separately.

Dimensions (approx. dimensions) H x W : 200 x 600 mm

Material thickness : 1.5 mm Cross-section distance : 300 mm

Delivery length : 6000 mm

Usable cross-section : 107995 mm²

Material : Steel, hot-dip galvanised to DIN EN ISO 1461

NIEDAX Model No. : WRU 200.600 F

EP Material_____ EP Wage_____

Technical Datasheet

Long Span Cable Tray

WRU 200.600 F

the photorealistic images are to be considered as reference images

Tender Text

Unit price/meter

Safety & Environment

REACH Date	23.01.2024
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73089059

Related items

Cover

Model No.	Description
WDRS 20 F	Turning bolt with locknut acc. to DIN EN ISO 10511, for WSL/WRL, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories
WDV 600 F	Cover for WSL/WRL, w. joint strip, 604x3000 mm, with turning lock, steel, hot dip galvanised DIN EN ISO 1461

Barrier strip

Model No.	Description
KLWC 16 F	Barrier strip fastening clamp, for 16 mm slot width, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories
RW 110 F	Barrier strip, 98x3000 mm, t=0,9 mm, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories

Connector

Model No.	Description
WSV 200.500 F	Splice plate, 201,5x500 mm, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories