



Crossing

with continuously perforated side profiles

KLK 60.203 E3

EAN Code: 4013339343300
Smallest packaging unit:1 pc.

the photorealistic images are to be considered as reference images



Article Description

Crossing for cable ladder, 60x200 mm, stainless steel, material code: 1.4301, AISI 304

Additional Price Information

Article group	N13
quantity unit	pcs.

Weight

Weight per quantity unit	9,893 kg / pcs.
Weight in kg per 100	989 kg / 100pcs.

Physical Article Dimensions

Height	120.00 mm
Width	1490 mm
Depth/length	1490 mm

Technical Datasheet

Cable Ladder System

KLK 60.203 E3

the photorealistic images are to be considered as reference images

Packing Dimension

1 piece = 1 piece		✓ VP1-smallest packaging unit (PU)			
Lenght	1490 mm	Width	1490 mm	Height	120.00 mm
Gross weight	9,89 kg	Volume	0,266 m³		
Min. quantity	1.00 pcs.	Max. Quantity	1.00 pcs.		

Tender Text

Crossing, with continuously perforated and profiled side beams, with riveted rungs made of C-profiles with 11 mm slot width, for creating horizontal 90° crossings.

Please order splice plates KSV 60... separately.

Suitable U-clamps (BA... as well as B...).

for cable ladder : KL 60...

Dimensions (approx. dimensions)

Height H x width W : 60 x 200 mm

Outside dimensions : 1290 mm + W

Length in outgoing direction : 645 mm + W

Inner beam radius R : 500 mm

Material : stainless steel, material no. 1.4301, AISI 304

NIEDAX Model no. : KLK 60.203 E3

EP Material_____ EP Wage_____

Unit price/piece

Safety & Environment

REACH Date	23.01.2024
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Federal State of Origin	RP
Customs tariff number	73089059

Related items

Connector

Model No.	Description
KSV 60 E3	Splice plate for cable ladder, height 60 mm, stainless steel, mat. code: 1.4301, AISI 304, washed,incl. accessories