


Support Rail Type 2934

Top hat profile 35 mm, TS 35 similar to DIN EN 60715, unperforated

2934/4 GO

EAN Code: 4013339026708
Smallest packaging unit: 10 x 4 m
quantity unit: m M

the photorealistic images are to be considered as reference images



Article Description

Support rail, top hat profile, 35x15x4000 mm, unperforated, steel, electro galvanised according to DIN EN ISO 2081, passivated

Weight

Weight per quantity unit	682 g / m
Weight in kg per 100	68 kg / 100m

Physical Article Dimensions

Height	15.00 mm
Width	35.00 mm
Depth/length	4000 mm

Technical Datasheet

Niedax rails

2934/4 GO

the photorealistic images are to be considered as reference images

Additional Price Information

Article group	N04
quantity unit	m

Packing Dimension

40 meters = 1 bundle		✓ VP1-smallest packaging unit (PU) ✓ VP1-preferred PU	
Gross weight	27 kg		
Min. quantity	40.00 m	Max. Quantity	40.00 m

Tender Text

Niedax mounting rail model 2934, mounting rail TS 35 connection dimensions acc. to DIN EN 60715, higher and thicker version, unperforated, electrogalvanised acc. to DIN EN ISO 2081, thick-film passivated, for quick fastening of installation devices and terminal blocks.

Dimensions (approx. dimensions) H x d : 15 x 1.5 mm

Fastening dimension W : 27 mm

TS Snap-on dimension B1 : 35 mm

Delivery length L : 4000 mm

NIEDAX Model No.: 2934/4 GO

EP Material_____ EP Wage_____

Unit price/meter

Safety & Environment

REACH Date	23.01.2024
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73269098