

Vertical Cable Ladder

rung spacing 300 mm, with continuously perforated side profiles



STL 60.203/6 E3

EAN Code: 4013339906550

Smallest packaging unit: 6 m

quantity unit: m M

the photorealistic images are to be considered as reference images



Article Description

Vertical cable ladder, 60x200x6000 mm, rung distance 300 mm, stainless steel, material code: 1.4301, AISI 304

Additional Price Information

Article group	N13
quantity unit	m

Weight

Weight per quantity unit	2,695 kg / m
Weight in kg per 100	269 kg / 100m

Technical Datasheet

Vertical Cable Ladder System

STL 60.203/6 E3

the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	60.00 mm
Width	199.00 mm
Depth/length	6000 mm

Packing Dimension

6 meters = 1 piece		✓ VP1-smallest packaging unit (PU)		✓ VP1-preferred PU	
Lenght	6000 mm	Width	199.00 mm	Height	60.00 mm
Gross weight	16 kg	Volume	0,072 m³		
Min. quantity	6.00 m	Max. Quantity	6.00 m		

Tender Text

Vertical cable ladder acc. to DIN EN 61537, for wall mounting, with continuously perforated and profiled side beams, with riveted rungs made of C-profiles with 16 mm slot width. Suitable U-clamps (B...).

For use in function maintenance, please observe additional instructions!

Dimensions (approx. dimensions)

Height H x Width W : 60 x 200 mm

Material thickness rail : 1.5 mm

Distance between rungs : 300 mm

Side beam perforation : 9 x 15 mm

centre distance : 25 mm

Bottom perforation : Ø 8.5 mm and Ø 5.4 mm

centre distance : 100 mm and 50 mm

Load capacity at B/2 : 1.0 kN

Delivery length L : 6000 mm

Usable cross section : 8500 mm²

Material : stainless steel, material no. 1.4301, AISI 304

NIEDAX Model No. : STL 60.203/6 E3

EP material_____ EP wage_____

Unit price/meter

Safety & Environment

REACH Date	23.01.2024
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73089059

Technical Datasheet

Vertical Cable Ladder System

STL 60.203/6 E3

the photorealistic images are to be considered as reference images

Related items

Barrier strip

Model No.	Description
KLWC 16 E3	Barrier strip fastening clamp, for 16 mm slot width, stainless steel, material code: 1.4301, AISI 304, incl. accessories
RW 35 E3	Barrier strip, 30x3000 mm, t=0,8 mm, stainless steel, material code: 1.4301, AISI 304, incl. accessories

Connector

Model No.	Description
KSV 60 E3	Splice plate for cable ladder, height 60 mm, stainless steel, mat. code: 1.4301, AISI 304, washed,incl. accessories