

Cable Ladder

made of oval, closed tubular profile bars and welded, closed, oval rungs




KRO 60.525 F

EAN Code: 4013339847006

Smallest packaging unit:6 m

quantity unit:m M

the photorealistic images are to be considered as reference images



Article Description

Cable ladder, 60x500x6000 mm, with closed, oval rungs, steel, hot dip galvanised DIN EN ISO 1461

Additional Price Information

Article group	N13
quantity unit	m

Weight

Weight per quantity unit	3,936 kg / m
Weight in kg per 100	394 kg / 100m

Physical Article Dimensions

Height	60.00 mm
Width	500 mm
Depth/length	6000 mm

Technical Datasheet


Cable Ladder System

KRO 60.525 F

the photorealistic images are to be considered as reference images

Load Specifications

Load diagram: q = evenly distributed cable load (tested acc. to DIN EN IEC 61537)



Packing Dimension

6 meters = 1 piece

✓ VP1-smallest packaging unit (PU) ✓ VP1-preferred PU

Lenght	6000 mm	Width	500 mm	Height	60.00 mm
Gross weight	24 kg	Volume	0,180 m³		
Min. quantity	6.00 m	Max. Quantity	6.00 m		

Tender Text

Cable ladder, acc. to DIN EN 61537, side beams made of hollow profiles, with welded-on, closed, oval rungs.
Dimensions (approx. dimensions) H x W : 60 x 500 mm
Material thickness : 1 mm Rung
distance : 250 mm
Delivery length L : 6000 mm
Usable cross-section : 17480 mm²
Material : Steel, hot-dip galvanised acc. to DIN EN ISO 1461
NIEDAX Model No. : KRO 60.525 F
EP Material _____ EP Wage _____
Unit price/meter

Safety & Environment

REACH Date	23.01.2024
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Federal State of Origin	RP
Customs tariff number	73089059

Technical Datasheet

Cable Ladder System

KRO 60.525 F

the photorealistic images are to be considered as reference images

Related items

Cover

Model No.	Description
KRD 500 F	Cover for cable ladder, width 506 mm, steel, hot dip galvanised DIN EN ISO 1461
KRDBK 60 F	Cover fastening clamp, steel, hot dip galvanised DIN EN ISO 1461

Barrier strip

Model No.	Description
KRTB 6 F	Fastening element for barrier strip/ mounting plate, steel, hot dip galvanised DIN EN ISO 1461
RW 35 F	Barrier strip, 30x3000 mm, t=0,75 mm, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories

Connector

Model No.	Description
KRLV 60 F	Splice plate, steel, hot dip galvanised DIN EN ISO 1461