

intercable

INSULATED TERMINALS

PC





Cu-ETP 99,9%, Sn / Copper tinned
PC
300V max.
T 120°C max.



mm²	Art.N.		mm				Pack
			d1	d4	l1	l2	
0,1-0,5	ICIQ05V	●	1,2	2,0	20,0	12,0	100
0,5-1	ICIQ1V	●	1,6	4,1	25,0	15,0	100
1,5-2,5	ICIQ2V	●	2,3	4,5	26,0	15,0	100
4-6	ICIQ6V	●	3,6	6,4	27,0	15,0	100

PA



Cu-ETP 99,9%, Sn / Copper tinned
PA 6.6 / Poliamide insulation
300V max.
T 105°C max.



mm²	Art.N.		mm				Pack
			d1	d4	l1	l2	
0,1-0,5	ICIQ05PV	●	1,2	2,0	12,0	5,0	100
0,5-1	ICIQ1PV	●	1,7	3,2	17,0	7,0	100
1,5-2,5	ICIQ2PV	●	2,3	4,0	17,0	7,0	100
4-6	ICIQ6PV	●	3,6	5,4	21,2	7,0	100

PE (thermo)



Cu-ETP 99,9%, Sn / Copper tinned
PE / Polietilene HD
300V max.
T -10 - 105°C max.



mm²	Art.N.		mm				Pack
			d1	d4	l1	l2	
0,1-0,5	ICIQ05WSV	●	1,4	3,1	24,5	11,5	100
0,5-1	ICIQ1WSV	●	1,7	4,4	36,0	15,0	100
1,5-2,5	ICIQ2WSV	●	2,3	5,2	36,0	15,0	100
4-6	ICIQ6WSV	●	3,6	6,5	41,0	15,0	100

typically used tools: „GENERAL CATALOG TOOLS“  6 - 16 mm² page: 136