


Cu - Intercable D standard / 90° „R-series“



Cu-HCP 99,9% / Copper tinned
DIN EN 13600



mm ²	Ø mm	Art. N. (inspect. hole: no)	mm						kg (/100)	Pack
			d1	d3	d2	b	l	a		
6	4	ICR6490	3,5	6,5	4,3	10	10,3	8	0,60	25
	5	ICR6590			5,3	11	11,3		0,62	25
	6	ICR6690			6,4	11	13,3		0,62	25
	8	ICR6890			8,4	15	15,3		0,64	25
	10	ICR61090			10,5	18	17,3		0,68	25
	12	ICR61290			13	20	18,3		0,66	25
10	5	ICR10590	4,5	7	5,3	12	11,5	9	0,54	25
	6	ICR10690			6,4	12	12,5		0,59	25
	8	ICR10890			8,4	15	15,5		0,67	25
	10	ICR101090			10,5	18	17,5		0,70	25
	12	ICR101290			13	20	18,5		0,70	25
16	5	ICR16590	5,5	8,5	5,3	12	13	12	1,07	25
	6	ICR16690			6,4	12	14,3		1,15	25
	8	ICR16890			8,4	15	16,3		1,20	25
	10	ICR161090			10,5	18	18,3		1,23	25
	12	ICR161290			13	20	19,3		1,23	25
25	6	ICR25690	7	10	6,4	15	15,5	14	1,48	25
	8	ICR25890			8,4	16	17,5		1,43	25
	10	ICR251090			10,5	18	19,5		1,68	25
	12	ICR251290			13	20	20,5		1,62	25
	14	ICR251490			15	22	22,5		2,07	25
35	6	ICR35690	8,5	12	6,4	17	16,5	16	2,10	25
	8	ICR35890			8,4	17	18,5		2,31	25
	10	ICR351090			10,5	20	20,5		2,39	25
	12	ICR351290			13	22	21,5		2,37	25
	14	ICR351490			15	23	23,5		2,48	25
50	16	ICR351690			17	28	24,5		2,48	25
	6	ICR50690	10	14	6,4	20	17,5	18	3,00	25
	8	ICR50890			8,4	20	19,5		3,22	25
	10	ICR501090			10,5	20	21,5		3,32	25
	12	ICR501290			13	23	22,5		3,28	25
	14	ICR501490			15	23	24,5		3,37	25
	16	ICR501690			17	27	28,5		3,77	25
	20	ICR502090			21	30	32,5		4,27	25