



Cu-HCP 99,9% / Copper tinned
DIN EN 13600



mm ²	cable min. Ø mm	Ø mm	Art. N. (inspect. hole: no)	mm						kg (/100)	Pack
				d1	d3	d2	b	l	a		
10	4,0	5	ICF105	5	8	5,3	12	23	12	0,70	50
		6	ICF106			6,4	12	25		0,76	50
		8	ICF108			8,4	15	28		0,91	50
		10	ICF1010			10,5	18	31		0,98	50
		12	ICF1012			13	20	32		1,00	50
16	5,0	5	ICF165	6	9	5,3	14	25,5	13	0,94	50
		6	ICF166			6,4	14	27		1,01	50
		8	ICF168			8,4	15	29,5		1,13	50
		10	ICF1610			10,5	18	32		1,14	50
		12	ICF1612			13	20	33		1,19	50
25	6,5	6	ICF256	7,7	10,7	6,4	16	32	16	1,51	50
		8	ICF258			8,4	16	34		1,50	50
		10	ICF2510			10,5	18	35		1,56	50
		12	ICF2512			13	20	36		1,65	50
35	7,8	6	ICF356	9,2	12,4	6,4	18	36	18	2,10	25
		8	ICF358			8,4	18	36		2,13	25
		10	ICF3510			10,5	18	38		2,14	25
		12	ICF3512			13	23	40		2,22	25
		16	ICF3516			17	26	45		2,21	25
50	9,0	6	ICF506	11,2	14,8	6,4	22	42	21	3,20	25
		8	ICF508			8,4	22	42		3,22	25
		10	ICF5010			10,5	22	43		3,36	25
		12	ICF5012			13	23	44		3,38	25
70	11,0	16	ICF5016			17	28	48,5		3,69	25
		6	ICF706	13,5	17,5	6,4	25	46	23	4,43	25
		8	ICF708			8,4	25	45,5		4,85	25
		10	ICF7010			10,5	25	47		5,00	25
		12	ICF7012			13	26	47		4,91	25
		16	ICF7016			17	28	50		5,15	25
		20	ICF7020			21	31	54,5		5,52	25