



Cu-HCP 99,9% / Copper tinned
DIN EN 13600



mm ²	cable min. Ø mm	Ø mm	Art. N. (inspect. hole: no)	mm						kg (/100)	Pack
				d1	d3	d2	b	l	a		
95	13,0	6	ICF956	15,5	20	6,4	29	50,5	26	6,50	25
		8	ICF958			8,4	29	50,5		6,93	25
		10	ICF9510			10,5	29	53		7,50	25
		12	ICF9512			13	29	52,5		7,08	25
		16	ICF9516			17	29	55		7,29	25
		20	ICF9520			21	35	60		7,61	25
120	15,0	10	ICF12010	16,8	21,3	10,5	31	56,5	29	8,19	25
		12	ICF12012			13	31	56		8,07	25
		16	ICF12016			17	31	58		8,36	25
		20	ICF12020			21	35	63		8,75	25
150	16,3	10	ICF15010	19	24	10,5	35	59	30	10,40	10
		12	ICF15012			13	35	58,5		10,70	10
		16	ICF15016			17	35	63		11,11	10
		20	ICF15020			21	35	66		11,96	10
185	18,5	10	ICF18510	21	26	10,5	38	67	35	13,59	10
		12	ICF18512			13	38	67		12,48	10
		16	ICF18516			17	38	69,5		12,88	10
		20	ICF18520			21	38	71		13,95	10
240	20,5	12	ICF24012	24	30	13	44	82	42	21,72	10
		16	ICF24016			17	44	85		21,94	10
		20	ICF24020			21	44	85		22,92	10
300	23,5	12	ICF30012	27,5	33,5	13	49	92	47	29,80	5
		16	ICF30016			17	49	92		27,50	5
		20	ICF30020			21	49	92		26,61	5