



Cu-HCP 99,9% / Copper tinned
DIN EN 13600



mm ²	Ø mm	Art. N. (inspect. hole: no)	mm						kg (/100)	Pack
			d1	d3	d2	b	l	a		
35	6	ICR356S	8,5	12	6,4	15	33	17	1,80	25
	8	ICR358S*			8,4	15	33	17	2,16	25
50	6	ICR506S	10	14	6,4	15	37	19	2,73	25
	8	ICR508S			8,4	17	39		2,83	25
	10	ICR5010S			10,5	17	41		2,99	25
70	6	ICR706S	11,8	16,5	6,4	17	41	21	4,06	25
	8	ICR708S			8,4	17	43		4,30	25
	10	ICR7010S			10,5	17	45		4,40	25
	12	ICR7012S			13	19	46		4,48	25
95	6	ICR956S	13,5	18	6,4	19	43	23	4,67	25
	8	ICR958S			8,4	19	45		4,90	25
	10	ICR9510S			10,5	19	47		5,10	25
	12	ICR9512S			13	19	48		5,20	25
120	6	ICR1206S	14,7	20	6,4	20	48	26	6,43	25
	8	ICR1208S			8,4	20	49		6,73	25
	10	ICR12010S			10,5	20	51		6,70	25
	12	ICR12012S			13	20	52		7,34	25
150	6	ICR1506S	16,3	21,3	6,4	19	53	29	7,11	10
	8	ICR1508S			8,4	19	51		7,11	10
	10	ICR15010S			10,5	19	53		7,34	10
	12	ICR15012S			13	22	59		7,63	10
185	10	ICR18510S	18,7	24	10,5	26	60	30	10,47	10
	12	ICR18512S			13	26	59,5		10,36	10
	16	ICR18516S			17	26	64		11,14	10
240	10	ICR24010S	21	26	10,5	30	65	35	11,96	10
	12	ICR24012S			13	30	65		12,19	10
	16	ICR24016S			17	30	68		12,26	10
300	10	ICR30010S	23,5	30	10,5	30	76	42	19,66	5
	12	ICR30012S			13	30	79		20,08	5
	16	ICR30016S			17	30	81		20,60	5