


Wide Span Cable Ladder

rung spacing 300 mm, with continuously perforated and beaded side profiles, with riveted, upwardly open C-profile rungs with 16 mm slot width

WSL 105.500 F

EAN Code: 4013339577903
Smallest packaging unit:6 m
quantity unit:m M

the photorealistic images are to be considered as reference images



Article Description

Wide span cable ladder, 105x500x6000 mm, t=1,5 mm, perforated, steel, hot dip galvanised DIN EN ISO 1461

Additional Price Information

Article group	N13
quantity unit	m

Weight

Weight per quantity unit	6,893 kg / m
Weight in kg per 100	689 kg / 100m

Technical Datasheet

Long Span Cable Ladder


WSL 105.500 F

the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	105.00 mm
Width	500 mm
Depth/length	6000 mm

Load Specifications



Packing Dimension

6 meters = 1 piece		✓ VP1-smallest packaging unit (PU)		✓ VP1-preferred PU	
Lenght	6000 mm	Width	500 mm	Height	105.00 mm
Gross weight	41 kg	Volume	0,315 m³		
Min. quantity	6.00 m	Max. Quantity	6.00 m		

Tender Text

Wide span cable ladder, acc. to DIN EN 61537, with continuous perforated and corrugated side beams and rungs riveted in C-profile with 16 mm slot width. Suitable U-clamps (B... and BK...) can be found in the KI catalogue. Please order splice plate WSV 105.390 separately.

Dimensions (approx. dimensions) H x W : 105 x 500 mm

Material thickness : 1.5 mm Rung distance : 300 mm

Side beam perforation : 9.5 x 13 mm

Hole distance : 50 mm

Delivery length : 6000 mm

Usable cross-section : 42685 mm²

Material : Steel, hot-dip galvanised acc. to DIN EN ISO 1461

NIEDAX Model No. : WSL 105.500 F

EP Material_____ EP Wage_____

Unit price/meter

Technical Datasheet

Long Span Cable Ladder

WSL 105.500 F

the photorealistic images are to be considered as reference images

Safety & Environment

REACH Date	27.06.2024
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73089059

Related items

Cover

Model No.	Description
WDRS 20 F	Turning bolt with locknut acc. to DIN EN ISO 10511, for WSL/WRL, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories
WDV 500 F	Cover for WSL/WRL, w. joint strip, 504x3000 mm, with turning lock, steel, hot dip galvanised DIN EN ISO 1461

Barrier strip

Model No.	Description
KLWC 16 F	Barrier strip fastening clamp, for 16 mm slot width, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories
RW 85 F	Barrier strip, 80x3000 mm, t=0,9 mm, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories

Connector

Model No.	Description
WSV 105.390 F	Splice plate, 106,5x390 mm, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories