


Vertical Cable Ladder

rung spacing 300 mm, with continuously perforated side profiles

STM 60.603/6

EAN Code: 4013339321704
 Smallest packaging unit:6 m
 quantity unit:m M

the photorealistic images are to be considered as reference images



Article Description

Vertical cable ladder, 60x600x6000 mm, rung distance 300 mm, steel, pre-galvanised according to DIN EN 10346

Additional Price Information

Article group	N13
quantity unit	m

Weight

Weight per quantity unit	5,657 kg / m
Weight in kg per 100	566 kg / 100m

Technical Datasheet

Vertical Cable Ladder System

STM 60.603/6

the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	60.00 mm
Width	599 mm
Depth/length	6000 mm

Packing Dimension

6 meters = 1 piece		✓ VP1-smallest packaging unit (PU)		✓ VP1-preferred PU	
Lenght	6000 mm	Width	599 mm	Height	60.00 mm
Gross weight	34 kg	Volume	0,216 m³		
Min. quantity	6.00 m	Max. Quantity	6.00 m		

Tender Text

Vertical cable ladder acc. to DIN EN 61537, for wall mounting, with continuously perforated and profiled side beams, with riveted rungs made of C-profiles with 18 mm slot width. Suitable U-clamps (BU... and BUK...). Please observe additional regulations for use in functional maintenance!

Dimensions (approx. dimensions) H x W : 60 x 600 mm

Material thickness beam : 2 mm Rung

distance : 300 mm

Side beam perforation : 9 x 15 mm

Centre distance : 25 mm

Bottom perforation : Ø 8.5 mm and Ø 5.4 mm Centre distance : 100 mm and 50 mm

Load capacity at B/2 : 1.75 kN

Delivery length L : 6000 mm

Usable cross-section : 21400 mm²

Material : Steel, pre-galvanised acc. to DIN EN 10346

NIEDAX Model No. : STM 60.603/6

EP Material_____ EP Wage_____

Unit price/meter

Safety & Environment

REACH Date	27.06.2024
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73089059

Related items

Cover

Model No.	Description
RDHFS 9 VZL	Cover clamp, steel, electro galvanised according to DIN EN ISO 2081, blue passivate
STVW 600 S	Vertical cable ladder cover, 203x609x3000 mm, wall mounting, steel, pre-galvanised according to DIN EN 10346, incl. accessories

Technical Datasheet

Vertical Cable Ladder System

STM 60.603/6

the photorealistic images are to be considered as reference images

Related items

Barrier strip

Model No.	Description
KLWC 18 F	Barrier strip fastening clamp, for 18 mm slot width, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories
RW 35	Barrier strip, 30x3000 mm, t=0,75 mm, steel, pre-galvanised according to DIN EN 10346, incl. accessories

Connector

Model No.	Description
KLVB 60/4	Splice plate, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories
KSV 60 S	Splice plate for cable ladder, height 60 mm, steel, pre-galvanised according to DIN EN 10346, incl. accessories