

	 ALFRA COMPACT®	 ALFRA COMPACT COMBI®	 ALFRA COMPACT FLEX®	 ALFRA AKKU-COMPACT FLEX®
Page	26 - 27	28 - 29	32	30 - 31
Prod.-No.	02001	02050	02065	02082
Punching Circular holes	up to 82 mm Ø 3.0 mm sheet steel (S235), 2.0 mm stainless steel (F = 600 N/mm ²)			
	89 - 152 mm Ø (with special draw bolt and spacer sleeve) 2.0 mm sheet steel (S235), 1.5 mm stainless steel (F = 600 N/mm ²)			
Punching Shaped holes	68 x 68 mm 3.0 mm sheet steel (S235), 2.0 mm stainless steel (F = 600 N/mm ²)			
	92 x 92 mm (with special draw bolt and spacer sleeve) 2.0 mm sheet steel (S235), 1.5 mm stainless steel (F = 600 N/mm ²)			
Punching force	75 kN	75 kN	75 kN	75 kN
Hydraulic pressure max.	680 bar	680 bar	680 bar	680 bar
Piston stroke	18 mm	18 mm	18 mm	18 mm
Tool mounting	19 mm	19 mm	19 mm	19 mm
Hydraulic hose length	-	-	600 mm	600 mm
Hydraulic medium	HLP32 hydraulic oil	HLP32 hydraulic oil	HLP32 hydraulic oil	HLP32 hydraulic oil
Weight	1.45 kg	1.75 kg	1.97 kg	2.5 kg with Battery