

Crimping dies for PA 4 and WZ 12

further dies are available on request!



dies for D-sub-connectors

for crimping D-sub-connectors **0.08 - 0.56 mm²**; contact and insulation crimping in one step.

art.-no.: 90779



dies for turned contacts

or crimping turned contacts (multipin plug connections)
plug-in-Ø **1.6 mm, 2.4 mm and 2.5 mm**,
cross section : **0.14 - 4.0 mm²**

art.-no.: 90781

for crimping turned contacts (multipin plug connections)
plug-in-Ø **1.6 mm, 2.4 mm and 2.5 mm**,
cross section: **1.5 - 6.0 mm²**

art.-no.: 90782



dies square-shape

for crimping insulated and noninsulated cord-end-sleeves **0.25 - 6 mm²**,
pressing width 12 mm

art.-no.: 90784

for crimping insulated and noninsulated cord-end-sleeves
10 - 25 mm², pressing width 12 mm

art.-no.: 90785

for crimping insulated and noninsulated cord-end-sleeves
35 - 50 mm², pressing width 12 mm (not suitable for PA 4)


art.-no.: 90786



dies square-shape

for crimping insulated twin-cord-end-sleeves **2 x 6 mm²**
up to **2 x 16 mm²**, pressing width 12 mm.

art.-no.: 90780



dies hexagonal shape

for crimping coax-connectors RG 58, RG 59, RG 62 und RG 71

art.-no.: 90788

for crimping coax-connectors RG 58 und RG 174

art.-no.: 90789